

## All Project Cargo Vehicle Configurations

### 8 Axle Configuration A1 PC 8-A1

| Axle No.             | 1     | 2                         | 3           | 4                        | 5              | 6           | 7           | 8              | GCVW   |
|----------------------|-------|---------------------------|-------------|--------------------------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive <sup>1</sup> |             | Single Jeep <sup>2</sup> | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 29,000                    |             |                          | 27,000         |             |             | 9,100          | 72,800 |
| No. of Tires         | 2     | 8                         |             | 4                        | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51               | 1.37 - 1.52 | 1.78 - 1.82              | 8.43 - 9.9     | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |
|                      |       | 1. Max. 23,000 kg         |             | 2. Max. 11,000 kg        |                |             |             |                |        |

### 8 Axle Configuration A2 PC 8-A2

| Axle No.             | 1     | 2                         | 3           | 4                        | 5              | 6           | 7           | 8              | GCVW   |
|----------------------|-------|---------------------------|-------------|--------------------------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive <sup>1</sup> |             | Single Jeep <sup>2</sup> | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 29,000                    |             |                          | 27,000         |             |             | 9,100          | 72,800 |
| No. of Tires         | 2     | 8                         |             | 4                        | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51               | 1.37 - 1.52 | 1.78 - 1.82              | 9.9 - 14.0     | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |
|                      |       | 1. Max. 23,000 kg         |             | 2. Max. 11,000 kg        |                |             |             |                |        |

### 8 Axle Configuration A3 PC 8-A3

| Axle No.             | 1     | 2                         | 3           | 4                        | 5              | 6           | 7           | 8              | GCVW   |
|----------------------|-------|---------------------------|-------------|--------------------------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive <sup>1</sup> |             | Single Jeep <sup>2</sup> | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 29,000                    |             |                          | 27,000         |             |             | 9,100          | 72,800 |
| No. of Tires         | 2     | 8                         |             | 4                        | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51               | 1.37 - 1.52 | 1.78 - 1.82              | 14.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |
|                      |       | 1. Max. 23,000 kg         |             | 2. Max. 11,000 kg        |                |             |             |                |        |

### 8 Axle Configuration B1 PC 8-B1

| Axle No.             | 1     | 2            | 3           | 4           | 5              | 6           | 7           | 8              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Single Jeep | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 11,000      | 27,000         |             |             | 9,100          | 77,800 |
| No. of Tires         | 2     | 8            |             | 4           | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 3.50 - 3.85 | 8.43 - 9.9     | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |

### 8 Axle Configuration B2 PC 8-B2

| Axle No.             | 1     | 2            | 3           | 4           | 5              | 6           | 7           | 8              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Single Jeep | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 11,000      | 27,000         |             |             | 9,100          | 77,800 |
| No. of Tires         | 2     | 8            |             | 4           | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 3.50 - 3.85 | 9.9 - 14.0     | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |

### 8 Axle Configuration B3 PC 8-B3

| Axle No.             | 1     | 2            | 3           | 4           | 5              | 6           | 7           | 8              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Single Jeep | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 11,000      | 27,000         |             |             | 9,100          | 77,800 |
| No. of Tires         | 2     | 8            |             | 4           | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 3.50 - 3.85 | 14.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |

### 8 Axle Configuration C1 PC 8-C1

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7    | 8              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tandem Trailer |      | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 23,000         |      | 9,100          | 85,800 |
| No. of Tires         | 2     | 8            |             | 8           |      | 8              |      | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 8.43 - 9.9     | 1.37 | 3.5 - 4.30     |        |

### 8 Axle Configuration C2 PC 8-C2

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7    | 8              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tandem Trailer |      | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 23,000         |      | 9,100          | 85,800 |
| No. of Tires         | 2     | 8            |             | 8           |      | 8              |      | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 9.9 - 14.0     | 1.37 | 3.5 - 4.30     |        |

### 8 Axle Configuration C3 PC 8-C3

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7    | 8              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tandem Trailer |      | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 23,000         |      | 9,100          | 85,800 |
| No. of Tires         | 2     | 8            |             | 8           |      | 8              |      | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 14.0 - 35.0    | 1.37 | 3.5 - 4.30     |        |

### 9 Axle Configuration A1 PC 9-A1

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7    | 8              | 9    | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|------|----------------|------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tandem Trailer |      | Tandem Booster |      |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 23,000         |      | 23,000         |      | 99,700 |
| No. of Tires         | 2     | 8            |             | 8           |      | 8              |      | 8              |      |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 8.53 - 9.9     | 1.37 | 4.27 - 4.57    | 1.37 |        |

**9 Axle Configuration A2 PC 9-A2**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7    | 8              | 9    | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|------|----------------|------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tandem Trailer |      | Tandem Booster |      |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 23,000         |      | 23,000         |      | 99,700 |
| No. of Tires         | 2     | 8            |             | 8           |      | 8              |      | 8              |      |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 9.9 - 14.0     | 1.37 | 4.27 - 4.57    | 1.37 |        |

**9 Axle Configuration A3 PC 9-A3**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7    | 8              | 9    | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|------|----------------|------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tandem Trailer |      | Tandem Booster |      |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 23,000         |      | 23,000         |      | 99,700 |
| No. of Tires         | 2     | 8            |             | 8           |      | 8              |      | 8              |      |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 14.0 - 35.0    | 1.37 | 4.27 - 4.57    | 1.37 |        |

**9 Axle Configuration B1 PC 9-B1**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7           | 8           | 9              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 27,000         |             |             | 9,100          | 89,800 |
| No. of Tires         | 2     | 8            |             | 8           |      | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 8.53 - 9.9     | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |

**9 Axle Configuration B2 PC 9-B2**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7           | 8           | 9              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 27,000         |             |             | 9,100          | 89,800 |
| No. of Tires         | 2     | 8            |             | 8           |      | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 9.9 - 14.0     | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |

**9 Axle Configuration B3 PC 9-B3**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7           | 8           | 9              | GCVW   |
|----------------------|-------|--------------|-------------|-------------|------|----------------|-------------|-------------|----------------|--------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tridem Trailer |             |             | Single Booster |        |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 27,000         |             |             | 9,100          | 89,800 |
| No. of Tires         | 2     | 8            |             | 8           |      | 12             |             |             | 4              |        |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 14.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 3.5 - 4.30     |        |

**10 Axle Configuration A1 PC 10-A1**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7           | 8           | 9              | 10   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 27,000         |             |             | 23,000         |      | 103,700 |
| No. of Tires         | 2     | 8            |             | 8           |      | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 9.75 - 14.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.37 |         |

**10 Axle Configuration A2 PC 10-A2**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7           | 8           | 9              | 10   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 27,000         |             |             | 23,000         |      | 103,700 |
| No. of Tires         | 2     | 8            |             | 8           |      | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 14.0 - 16.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.37 |         |

**10 Axle Configuration A3 PC 10-A3**

| Axle No.             | 1     | 2            | 3           | 4           | 5    | 6              | 7           | 8           | 9              | 10   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tandem Jeep |      | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 23,000      |      | 27,000         |             |             | 23,000         |      | 103,700 |
| No. of Tires         | 2     | 8            |             | 8           |      | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 4.59 | 1.37 | 16.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.37 |         |

**10 Axle Configuration B1 PC 10-B1**

| Axle No.             | 1     | 2            | 3          | 4           | 5           | 6              | 7          | 8              | 9           | 10   | GCVW    |
|----------------------|-------|--------------|------------|-------------|-------------|----------------|------------|----------------|-------------|------|---------|
| Axle Description     | Steer | Tridem Drive |            | Tandem Jeep |             | Tandem Trailer |            | Tandem Booster |             |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |            | 23,000      |             | 23,000         |            | 23,000         |             |      | 103,700 |
| No. of Tires         | 2     | 12           |            | 8           |             | 8              |            | 8              |             |      |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.4 | 1.37 - 1.4  | 4.27 - 4.59 | 1.37           | 8.53 - 9.9 | 1.37           | 4.27 - 4.57 | 1.37 |         |

**10 Axle Configuration B2 PC 10-B2**

| Axle No.             | 1     | 2            | 3          | 4           | 5           | 6              | 7          | 8              | 9           | 10   | GCVW    |
|----------------------|-------|--------------|------------|-------------|-------------|----------------|------------|----------------|-------------|------|---------|
| Axle Description     | Steer | Tridem Drive |            | Tandem Jeep |             | Tandem Trailer |            | Tandem Booster |             |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |            | 23,000      |             | 23,000         |            | 23,000         |             |      | 103,700 |
| No. of Tires         | 2     | 12           |            | 8           |             | 8              |            | 8              |             |      |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.4 | 1.37 - 1.4  | 4.27 - 4.59 | 1.37           | 9.9 - 14.0 | 1.37           | 4.27 - 4.57 | 1.37 |         |

**10 Axle Configuration B3 PC 10-B3**

| Axle No.             | 1     | 2            | 3          | 4           | 5           | 6              | 7           | 8              | 9           | 10   | GCVW    |
|----------------------|-------|--------------|------------|-------------|-------------|----------------|-------------|----------------|-------------|------|---------|
| Axle Description     | Steer | Tridem Drive |            | Tandem Jeep |             | Tandem Trailer |             | Tandem Booster |             |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |            | 23,000      |             | 23,000         |             | 23,000         |             |      | 103,700 |
| No. of Tires         | 2     | 12           |            | 8           |             | 8              |             | 8              |             |      |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.4 | 1.37 - 1.4  | 4.27 - 4.59 | 1.37           | 14.0 - 35.0 | 1.37           | 4.27 - 4.57 | 1.37 |         |

**11 Axle Configuration A1 PC 11-A1**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7              | 8           | 9           | 10             | 11   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tridem Jeep |             |             | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 27,000      |             |             | 27,000         |             |             | 23,000         |      | 107,700 |
| No. of Tires         | 2     | 8            |             | 12          |             |             | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 4.39 - 5.61  | 1.37 - 1.52 | 4.22 - 5.30 | 1.37 - 1.52 | 1.37 - 1.52 | 9.75 - 14.0    | 1.37 - 1.52 | 1.37 - 1.52 | 3.7 - 4.57     | 1.37 |         |

**11 Axle Configuration A2 PC 11-A2**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7              | 8           | 9           | 10             | 11   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tridem Jeep |             |             | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 27,000      |             |             | 27,000         |             |             | 23,000         |      | 107,700 |
| No. of Tires         | 2     | 8            |             | 12          |             |             | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 4.39 - 5.61  | 1.37 - 1.52 | 4.22 - 5.30 | 1.37 - 1.52 | 1.37 - 1.52 | 14.0 - 18.0    | 1.37 - 1.52 | 1.37 - 1.52 | 3.7 - 4.57     | 1.37 |         |

**11 Axle Configuration A3 PC 11-A3**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7              | 8           | 9           | 10             | 11   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tridem Jeep |             |             | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 27,000      |             |             | 27,000         |             |             | 23,000         |      | 107,700 |
| No. of Tires         | 2     | 8            |             | 12          |             |             | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 4.39 - 5.61  | 1.37 - 1.52 | 4.22 - 5.30 | 1.37 - 1.52 | 1.37 - 1.52 | 18.0 - 35.0    | 1.37 - 1.52 | 1.37 - 1.52 | 3.7 - 4.57     | 1.37 |         |

**11 Axle Configuration B1 PC 11-B1**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6    | 7              | 8           | 9           | 10             | 11   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tridem Drive |             | Tandem Jeep |             |      | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             | 23,000      |             |      | 27,000         |             |             | 23,000         |      | 107,700 |
| No. of Tires         | 2     | 12           |             | 8           |             |      | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 4.59 | 1.37 | 9.75 - 14.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.37 |         |

**11 Axle Configuration B2 PC 11-B2**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6    | 7              | 8           | 9           | 10             | 11   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tridem Drive |             | Tandem Jeep |             |      | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             | 23,000      |             |      | 27,000         |             |             | 23,000         |      | 107,700 |
| No. of Tires         | 2     | 12           |             | 8           |             |      | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 4.59 | 1.37 | 14.0 - 18.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.37 |         |

**11 Axle Configuration B3 PC 11-B3**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6    | 7              | 8           | 9           | 10             | 11   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|------|----------------|-------------|-------------|----------------|------|---------|
| Axle Description     | Steer | Tridem Drive |             | Tandem Jeep |             |      | Tridem Trailer |             |             | Tandem Booster |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             | 23,000      |             |      | 27,000         |             |             | 23,000         |      | 107,700 |
| No. of Tires         | 2     | 12           |             | 8           |             |      | 12             |             |             | 8              |      |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 4.59 | 1.37 | 18.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.37 |         |

**12 Axle Configuration A1 PC 12-A1**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7              | 8           | 9           | 10             | 11          | 12          | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tridem Jeep |             |             | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 27,000      |             |             | 27,000         |             |             | 27,000         |             |             | 111,700 |
| No. of Tires         | 2     | 8            |             | 12          |             |             | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 9.75 - 14.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**12 Axle Configuration A2 PC 12-A2**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7              | 8           | 9           | 10             | 11          | 12          | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tridem Jeep |             |             | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 27,000      |             |             | 27,000         |             |             | 27,000         |             |             | 111,700 |
| No. of Tires         | 2     | 8            |             | 12          |             |             | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 14.0 - 18.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**12 Axle Configuration A3 PC 12-A3**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7              | 8           | 9           | 10             | 11          | 12          | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tandem Drive |             | Tridem Jeep |             |             | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 27,000      |             |             | 27,000         |             |             | 27,000         |             |             | 111,700 |
| No. of Tires         | 2     | 8            |             | 12          |             |             | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 4.39 - 5.51  | 1.37 - 1.52 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 18.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**12 Axle Configuration B1 PC 12-B1**

| Axle No.             | 1     | 2            | 3          | 4           | 5           | 6    | 7              | 8           | 9           | 10             | 11          | 12          | GCVW    |
|----------------------|-------|--------------|------------|-------------|-------------|------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tridem Drive |            | Tandem Jeep |             |      | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |            | 23,000      |             |      | 27,000         |             |             | 27,000         |             |             | 111,700 |
| No. of Tires         | 2     | 12           |            | 8           |             |      | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.4 | 1.37 - 1.4  | 4.27 - 4.59 | 1.37 | 9.75 - 14.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**12 Axle Configuration B2 PC 12-B2**

| Axle No.             | 1     | 2            | 3          | 4          | 5           | 6    | 7              | 8           | 9           | 10             | 11          | 12          | GCVW    |
|----------------------|-------|--------------|------------|------------|-------------|------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tridem Drive |            |            | Tandem Jeep |      | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |            |            | 23,000      |      | 27,000         |             |             | 27,000         |             |             | 111,700 |
| No. of Tires         | 2     | 12           |            |            | 8           |      | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.4 | 1.37 - 1.4 | 4.27 - 4.59 | 1.37 | 14.0 - 18.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**12 Axle Configuration B3 PC 12-B3**

| Axle No.             | 1     | 2            | 3          | 4          | 5           | 6    | 7              | 8           | 9           | 10             | 11          | 12          | GCVW    |
|----------------------|-------|--------------|------------|------------|-------------|------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tridem Drive |            |            | Tandem Jeep |      | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |            |            | 23,000      |      | 27,000         |             |             | 27,000         |             |             | 111,700 |
| No. of Tires         | 2     | 12           |            |            | 8           |      | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 5.4 - 5.5    | 1.37 - 1.4 | 1.37 - 1.4 | 4.27 - 4.59 | 1.37 | 18.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**13 Axle Configuration A1 PC 13-A1**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9           | 10          | 11             | 12          | 13          | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tridem Drive |             |             | Tridem Jeep |             |             | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             |             | 27,000      |             |             | 27,000         |             |             | 27,000         |             |             | 115,700 |
| No. of Tires         | 2     | 12           |             |             | 12          |             |             | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 5.2 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 9.75 - 14.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**13 Axle Configuration A2 PC 13-A2**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9    | 10   | 11             | 12   | 13   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|------|------|----------------|------|------|---------|
| Axle Description     | Steer | Tridem Drive |             |             | Tridem Jeep |             |             | Tridem Trailer |      |      | Tridem Booster |      |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             |             | 27,000      |             |             | 27,000         |      |      | 27,000         |      |      | 115,700 |
| No. of Tires         | 2     | 12           |             |             | 12          |             |             | 12             |      |      | 12             |      |      |         |
| Spacing (m)          |       | 5.2 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 14.0 - 18.0    | 1.40 | 1.40 | 4.27           | 1.40 | 1.40 |         |

**13 Axle Configuration A3 PC 13-A3**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9    | 10   | 11             | 12   | 13   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|------|------|----------------|------|------|---------|
| Axle Description     | Steer | Tridem Drive |             |             | Tridem Jeep |             |             | Tridem Trailer |      |      | Tridem Booster |      |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             |             | 27,000      |             |             | 27,000         |      |      | 27,000         |      |      | 115,700 |
| No. of Tires         | 2     | 12           |             |             | 12          |             |             | 12             |      |      | 12             |      |      |         |
| Spacing (m)          |       | 5.2 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 18.0 - 35.0    | 1.40 | 1.40 | 4.27           | 1.40 | 1.40 |         |

**13 Axle Configuration B1 PC 13-B1**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9           | 10          | 11             | 12          | 13          | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tandem Drive |             | Single Jeep | Tridem Jeep |             |             | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 6,000       | 27,000      |             |             | 27,000         |             |             | 27,000         |             |             | 117,700 |
| No. of Tires         | 2     | 8            |             | 4           | 12          |             |             | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 4.78 - 5.27  | 1.37 - 1.52 | 1.82        | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 9.75 - 14.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**13 Axle Configuration B2 PC 13-B2**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9           | 10          | 11             | 12          | 13          | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tandem Drive |             | Single Jeep | Tridem Jeep |             |             | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 6,000       | 27,000      |             |             | 27,000         |             |             | 27,000         |             |             | 117,700 |
| No. of Tires         | 2     | 8            |             | 4           | 12          |             |             | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 4.78 - 5.27  | 1.37 - 1.52 | 1.82        | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 14.0 - 18.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**13 Axle Configuration B3 PC 13-B3**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9           | 10          | 11             | 12          | 13          | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|-------------|-------------|----------------|-------------|-------------|---------|
| Axle Description     | Steer | Tandem Drive |             | Single Jeep | Tridem Jeep |             |             | Tridem Trailer |             |             | Tridem Booster |             |             |         |
| Max Axle Weight (kg) | 7,700 | 23,000       |             | 6,000       | 27,000      |             |             | 27,000         |             |             | 27,000         |             |             | 117,700 |
| No. of Tires         | 2     | 8            |             | 4           | 12          |             |             | 12             |             |             | 12             |             |             |         |
| Spacing (m)          |       | 4.78 - 5.27  | 1.37 - 1.52 | 1.82        | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 18.0 - 35.0    | 1.40 - 1.52 | 1.40 - 1.52 | 4.27 - 4.57    | 1.40 - 1.52 | 1.40 - 1.52 |         |

**13 Axle Configuration C1 PC 13-C1**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9    | 10   | 11             | 12   | 13   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|------|------|----------------|------|------|---------|
| Axle Description     | Steer | Tridem Drive |             |             | Tridem Jeep |             |             | Tridem Group 1 |      |      | Tridem Group 2 |      |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             |             | 27,000      |             |             | 27,000         |      |      | 27,000         |      |      | 115,700 |
| No. of Tires         | 2     | 12           |             |             | 12          |             |             | 12             |      |      | 12             |      |      |         |
| Spacing 1 (m)        |       | 5.2 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 10.67 - 14.0   | 1.52 | 1.52 | 4.27 - 4.57    | 1.52 | 1.52 |         |

**13 Axle Configuration C2 PC 13-C2**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9    | 10   | 11             | 12   | 13   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|------|------|----------------|------|------|---------|
| Axle Description     | Steer | Tridem Drive |             |             | Tridem Jeep |             |             | Tridem Group 1 |      |      | Tridem Group 2 |      |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             |             | 27,000      |             |             | 27,000         |      |      | 27,000         |      |      | 115,700 |
| No. of Tires         | 2     | 12           |             |             | 12          |             |             | 12             |      |      | 12             |      |      |         |
| Spacing 1 (m)        |       | 5.2 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 14.0 - 18.0    | 1.52 | 1.52 | 4.27 - 4.57    | 1.52 | 1.52 |         |

**13 Axle Configuration C3 PC 13-C3**

| Axle No.             | 1     | 2            | 3           | 4           | 5           | 6           | 7           | 8              | 9    | 10   | 11             | 12   | 13   | GCVW    |
|----------------------|-------|--------------|-------------|-------------|-------------|-------------|-------------|----------------|------|------|----------------|------|------|---------|
| Axle Description     | Steer | Tridem Drive |             |             | Tridem Jeep |             |             | Tridem Group 1 |      |      | Tridem Group 2 |      |      |         |
| Max Axle Weight (kg) | 7,700 | 27,000       |             |             | 27,000      |             |             | 27,000         |      |      | 27,000         |      |      | 115,700 |
| No. of Tires         | 2     | 12           |             |             | 12          |             |             | 12             |      |      | 12             |      |      |         |
| Spacing 1 (m)        |       | 5.2 - 5.5    | 1.37 - 1.40 | 1.37 - 1.40 | 4.27 - 5.30 | 1.40 - 1.52 | 1.40 - 1.52 | 18.0 - 35.0    | 1.52 | 1.52 | 4.27 - 4.57    | 1.52 | 1.52 |         |