

INCLINATION: -90°

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, cm/s				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH				WATER CONTENT PERCENT					
								Cu, kPa		nat V. rem V.		+				Q - U -	
0		GROUND SURFACE		0.00											Steel stick-up well protector.		
1		Damp greyish-brown SILTY SAND, some clay, trace gravel, no hydrocarbon staining or odours.			1	AS											
2					2	AS											
3					3	AS											
4		Moist brown SAND, trace gravel, no hydrocarbon staining or odours.		2.44	4	AS											
5					5	AS											
6					6	AS											
7		Moist greyish-brown SANDY SILT, trace gravel, no hydrocarbon staining or odours.		3.66	7	AS											
8					8	AS											
9					9	AS											
10		Moist greyish-brown SANDY SILT, some gravel to gravelly, no hydrocarbon staining or odour.		5.49	10	AS											
11					11	AS											
12					12	AS											
13					13	AS											
14		Wet greyish-brown SANDY SILT, trace gravel, no hydrocarbon staining or odour		9.45	14	AS											
15					15	AS											
16					16	AS											
17		End of MONITORING WELL.		11.89													

Beck Drilling
CME's Auger Drill Rig

Pre-pack 8/16 filter sand with 38 mm (inner) diameter PVC pipe and 0.25 mm slotted screen.
06/06/08
8/16 filter sand.

BOREHOLE ARCO MW08-01.GPJ GLDR_CAN.GDT 16/2/09

