

SEACOR JOB NO: K0002-174

| DEPTH (m) | SAMPLE TYPE | SOIL TYPE | SOIL DESCRIPTION | TEST DATA | | | | WELL COMPLETION | WATER LEVEL | FIELD NOTES | DEPTH (m) | |
|-----------|-------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-----|------|-------|-----------------|-------------|-------------------------------------------|-----------|--|
| | | | | HYDROCARBON VAPOUR LEVEL (ppmv) | | | | | | | | |
| | | | | 10 | 100 | 1000 | 10000 | | | | | |
| 0.0 - 1.0 | | | SAND (Fill) - fine to medium-grained, silty, compact, brown, moist | | | | | | | Roadbox & concrete Bentonite seal | 0.0 - 1.0 | |
| 1.0 - 2.0 | | | | | | | | | | | 2.0 | |
| 2.0 - 3.0 | | | - trace fine-grained gravel at 2.3 m | | | | | | | Solid pipe backfilled with drill cuttings | 2.0 - 3.0 | |
| 3.0 - 4.0 | | | SAND (Native) - fine to medium-grained, micaceous, trace slit, trace clay, dense, brown, moist | | | | | | | | 3.0 | |
| 4.0 - 5.0 | | | | | | | | | | Bentonite seal | 4.0 - 5.0 | |
| 5.0 - 6.0 | | | - trace coarse-grained sand, trace fine-grained gravel at 5.5 m | | | | | | | | 5.0 | |
| 6.0 - 7.0 | | | | | | | | | | 010 well screen packed with silica sand | 6.0 - 7.0 | |
| 7.0 - 8.0 | | | - becomes wet at 6.9 m | | | | | | | | 7.0 | |
| 8.0 - 9.0 | | | - becomes saturated, grey at 7.6 m | | | | | | | Water level = 7.06 m | 8.0 - 9.0 | |
| 9.0 - 9.6 | | | | | | | | | | | 9.0 | |
| | | | End of borehole at 9.6 m Screened interval = 4.6 m to 9.1 m Elevation of top of piezometer (T.O.P.) = 99.66 m Groundwater elevation = 92.67 m Borehole combustible vapour level = 1000 ppmv (Mar./98) | | | | | | | | | |

DRILLING METHOD: Hollow Stem: Logged by TS
DATE DRILLED: 2/20/98

Notes: NO RECOVERY
 AUGER SAMPLE
 SPLIT SPOON SAMPLE
 CONTINUOUS SAMPLE