

B.C. ENERGY EFFICIENCY ACT STANDARDS: Electric Water Heaters

MEMPR INFORMATION BULLETIN 09-04



What products are you regulating? Electric storage-type water heaters with a rated storage capacity of 50 to 454 litres.

Are you forcing me to replace my water heater? No. The regulation applies to voluntary purchases of new or replacement water heaters. Individuals can keep their existing water heaters for as long as they wish.

What is the regulated energy efficiency standard for those products?

The standby loss (in watts)¹ must be equal to or less than:

$$25 + (0.20 \times V) \quad \text{for those having a top inlet and a rated volume}^2 \text{ of 50 to 270 litres or}$$

$$(0.472 \times V) - 48.5 \quad \text{for those having a top inlet and a rated volume of } >270 \text{ and } \leq 454 \text{ litres}$$

The maximum standby loss for water heaters with a bottom inlet³ is identical to existing federal standards set by Natural Resources Canada.

The standby loss (in watts) must be equal to or less than:

$$40 + (0.20 \times V) \quad \text{for those having a bottom inlet and a rated volume of 50 to 270 litres or}$$

$$(0.472 \times V) - 33.5 \quad \text{for those having a bottom inlet and a rated volume of } >270 \text{ and } \leq 454 \text{ litres}$$

Here is the new maximum Standby Loss levels for several common sizes:

Rated Storage Capacity in litres (imperial gallons)	Maximum Standby Loss For Top Inlet	Maximum Standby Loss for Bottom Inlet
114 L (25 imp gal)	48	63
136 L (30 imp gal)	52	67
182 L (40 imp gal)	61	76
272 L (60 imp gal)	80	95
364 L (80 imp gal)	123	138

For a lookup table with all sizes, go to:

www.empr.gov.bc.ca/EEC/Strategy/EEA/Pages/default.aspx

What are the new installation requirements for electric water heaters?

Homeowners and installers should be aware that all electric storage-type water heaters must have a functioning heat trap⁴ installed at the inlet and outlet, or, in the case of bottom inlet water heaters, at the outlet.

In addition, all water heaters must be installed with R-4 (RSI 0.70) pipe insulation on the first 3.0 metres (9.8 ft) of exposed⁵ outlet piping down stream of the tank or heat trap and the first 3.0 m of exposed water inlet piping upstream of the tank or heat trap. If there is an

