TYPICAL SIGN WIDTH	SPACING OF VERTICAL T-SECTIONS (SEE NOTE 3)	NUMBER OF VERTICALS
7320mm	610+ - 1220 + 1220 + 1220 + 1220 + 1220 + 610	6
6710mm	505	5
6100mm	600	5
5490mm	600 1430 1430 600	4
4880mm	610	4
4270mm	33512001200335	4
3660mm	430	3
3050mm	SIGN OUTLINE 325- -1200- -325 (TYPICAL)	3
2440mm	VERTICAL 'T'-SECTION (TYPICAL)	2

- NOTES

 1. SEE MATERIAL STANDARD SPECIFICATIONS CHAPTER 306 CANTILEVER AND SIGN BRIDGE STRUCTURES FOR ADDITIONAL INFORMATION.
- 2. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE NOTED.
- 3. T—SECTION SPACING FOR WIDER SIGNS WILL BE NOTED IN SPECIAL PROVISIONS.

NOT TO SCALE

No.	Description	Date	
J			1
-			1
Н			1
G			1
F			
Ε			1
D			1
С			Ь_
В			1
Α			1
REVISION			1

GENERIC EXTRUDED ALUMINUM SIGN MOUNTING FOR GENERIC CANTILEVER AND SIGN BRIDGE STRUCTURES

VERTICAL T-SECTION SIGN SUPPORT SPACING



Ministry of Transportation and Highways

MS351.4