Meager Creek Slim Holes Photographic and Condensed Core Records L1-L8 and M6-M14

(w/ Dr. J. Souther, G.S.C., Vancouver)

This report was prepared for the British Columbia Hydro and Power Authority ("BC Hydro"). BC Hydro does not:

- (a) represent, guarantee or warrant to any third party, either expressly or by implication: (i) the accuracy, completeness or usefulness of; (ii) the intellectual or other property rights of any person or party in; or (iii) the merchantability, safety or fitness for purpose of; any information, product or process disclosed, described or recommended in this report,
- (b) assume any liability of any kind arising in any way out of the use by a third party of any information, product or process disclosed, described or recommended in this report, or any liability arising out of reliance by a third party upon any information, statements or recommendations contained in this report.

Should third parties use or rely on any information, product or process disclosed, described or recommended in this report, they do so entirely at their own risk.

as per core boxes

M6-79D

M7-79D

M8-79D

M9-80D

M10-80D

M11-80D

M12-80D

M13-81D

M14-81D



PETROLEUM RESOURCES

M6 PHOTO LOG

Picture #	Box's	<pre>Intervals (m)</pre>
1	1-4	37.3 - 51.4
2	5-8	51.4 - 67.4
3	9-12	67.4 - 83.3
4	13-16	83.3 - 99.5
5	17-20	99.5 - 115.3
6	21-24	115.3 - 131.8
7	25 - 28	131.8 - 148.4
8	29-32	148.4 - 164.9
9	33-36	164.9 - 181.1
10	37-40	181.1 - 197.3
11	41-44	197.3 - 213.6
12	45-48	213.6 - 229.9
13	49-52	229.9 - 246.7
14	53-56	246.7 - 262.1
15	57 - 61	262.1 - 284.6
16	62-65	284.6 - 314.5
17	66	344.5 - 321.0

N.B. Box "58" is missing due to misnumbering of boxes. (Reduced to B at 266m)

M6 CONDENSED

Box #	<pre>Intervals (m)</pre>	Box #	<pre>Intervals (m)</pre>
1	37.3 - 38.5 40.8 - 42.1 44.2 - 45.5	11	157.4 - 157.8 160.7 - 162.3 164.9 - 166.0
2	50.0 - 51.4 51.4 - 53.0 56.0 - 57.4	12	171.8 - 173.0 173.0 - 174.5 177.3 - 178.6
3	60.8 - 62.2 63.8 - 65.0 67.4 - 68.5	13	181.1 - 182.4 186.5 - 187.9 189.2 - 190.3
4	71.0 - 72.3 75.0 - 76.3 79.1 - 80.5	14	193.1 - 194.4 197.3 - 198.6 201.6 - 203.0
5 ,	84.5 - 86.0 87.3 - 88.4 91.3 - 92.5	15	208.3 - 209.6 209.6 - 210.8 213.6 - 215.0
6	95.2 - 96.9 99.5 - 100.8 103.5 - 104.6	16	217.8 - 219.2 221.6 - 222.8 225.8 - 227.1
7	107.3 - 108.7 111.5 - 112.7 115.3 - 116.7	17	229.9 - 231.3 233.9 - 235.5 238.2 - 239.5
8	119.8 - 120.7 123.6 - 125.0 127.8 - 129.3	18	242.5 - 243.9 246.7 - 248.0 250.4 - 251.7
9	131.8 - 133.1 135.8 - 137.1 140.0 - 141.5	19	254.2 - 255.7 258.5 - 262.1 263.1 - 264.4
10	144.2 - 145.7 148.4 - 149.6 152.5 - 153.7	20	266.0 - 267.5 270.0 - 271.5 277.5 - 279.0 284.6 - 286.5 293.2 - 294.6
		21	300.5 - 302.0 307.5 - 309.0 314.5 - 316.0

M6 HEAT FLOW CONDUCTIVITY SAMPLES (m)

M7-79D PHOTO LOG

Picture #	Box's	<pre>Intervals (m)</pre>
1	1-4	33.5 - 48.8
2	5–8	48.8 - 66.8
3	9-12	66.8 - 81.6
4	13-16	81.6 - 97.8
5	17-20	97.8 - 117.1
6	21-24	117.1 - 132.3
7	25-28	132.3 - 148.2
8	29-32	148.2 - 163.5
9	33-36	163.5 - 179.1
10	37-40	179.1 - 195.4
11	41-44	195.4 - 211.5
12	45-48	211.5 - 227.7
13	49-52	227.7 - 243.6
14	53-56	243.6 - 259.6
15	57-60	259.6 - 275.2
16	61-64	275.2 - 290.7
17	65-68	290.7 - 306.1
18	69-72	306.1 - 322.1
19	73-76	322.1 - 340.3
20	77–80	340.3 - 356.5
21	81-83	356.5 - 367.0

M7-79D CONDENSED

Box #	<pre>Intervals (m)</pre>	Box #	<pre>Intervals (m)</pre>
1	33.5 - 34.9 37.4 - 38.1 41.2 - 42.6	12	167.4 - 168.6 171.0 - 172.2 175.2 - 178.6
2	45.1 - 46.5 48.8 - 50.1 52.9 - 54.2	13	180.5 - 181.5 182.9 - 184.1 187.1 - 188.5
3	58.5 - 59.9 62.5 - 63.9 66.8 - 68.1	14	191.2 - 192.5 195.4 - 196.7 199.4 - 200.3
4	70.7 - 71.7 74.0 - 75.5 77.7 - 78.6	15	203.5 - 205.0 207.7 - 208.7 211.5 - 213.0
5	83.0 - 84.2 85.8 - 87.1 89.3 - 90.8	16	223.6 - 224.7 219.4 - 220.8 215.7 - 217.0
6	93.6 - 95.0 97.8 - 103.1 105.6 - 106.8	17	227.7 - 229.1 232.0 - 233.2 235.6 - 237.4
7	109.6 - 110.6 113.0 - 114.8 117.1 - 118.2	18	239.7 - 240.8 243.6 - 244.8 247.5 - 249.0
8	120.6 - 122.0 124.3 - 125.7 128.3 - 129.9	19	251.2 - 252.6 255.3 - 256.8 259.6 - 260.9
9	132.3 - 133.4 136.1 - 137.3 139.9 - 141.1	20	263.5 - 264.7 267.7 - 268.8 271.5 - 273.0
10	144.2 - 145.3 148.2 - 149.5 152.1 - 153.1	. 21	275.2 - 276.6 279.2 - 280.4 283.3 - 284.5
11	155.7 - 157.2 159.7 - 161.0 163.5 - 164.8	22	287.0 - 288.4 290.7 - 292.2 294.5 - 295.7

Box #	Intervals (ft)
23	298.3 - 299.3 302.0 - 303.5 306.1 - 307.5
24	310.6 - 312.0 315.7 - 316.8 317.8 - 319.3
25	324.5 - 326.0 330.6 - 332.0 332.0 - 333.5
26	336.2 - 337.7 340.3 - 341.7 345.5 - 346.8
27	348.7 - 350.0 352.7 - 354.1 356.5 - 357.0
28	360.6 - 362.1 365.0 - 366.5

M7-79D HEAT FLOW CONDUCTIVITY SAMPLES (m)

(None to 33m)

(T.D. = 367m)

M8-79D PHOTO LOG

Picture #	Box #'s	Intervals (m)
1	1-4	11.1 - 28.5
2	5–8	28.5 - 44.6
3	9-12	44.6 - 60.5
4	13-16	60.5 - 76.3
5	17-20	76.3 - 92.3
6	21-24	92.3 - 107.5
7	25-28	107.5 - 123.0
8	29-32	123.0 - 138.4
9	33-36	138.4 - 153.7
10	37-40	153.7 - 169.5
11	41-44	169.5 - 183.3
12	45-48	183.3 - 198.9
13	49-52	198.9 - 215.1
14	53–56	215.1 - 231.5
15	57-60	231.5 - 248.4
16	61-64	248.4 - 263.2
17	65–68	263.2 - 279.3
18	69,70,71,El	279.3 - 294.5
19	E2-E5	294.5 - 310.8
20	E6-E9	310.8 - 326.9
21	E10-E13	326.9 - 343.3
22	E14-E17	343.3 - 359.8
23 ·	E18-E21	359.8 - 376.4
24	E22-E25	376.4 - 392.9
25	E26-E29	392.9 - 409.6
26	E30-E33	409.6 - 426.1
27	E34-E37	426.1 - 442.1
28	E38-E41	442.1 - 458.4
29	E42-E45	458.4 - 474.3
30	E46-E49	474.3 - 489.8
31	E50-E51	489.8 - 497.0 (T.D.)

M8-79D CONDENSED

Box	<pre>Intervals (m)</pre>	Box	Intervals (m)
1	11.1 - 12.4 15.2 - 16.6 19.5 - 20.8	12	142.3 - 143.6 146.9 - 147.8 150.0 - 150.8
2	23.6 - 25.0 28.5 - 30.0 32.7 - 34.0	13	153.7 - 154.8 157.0 - 158.4 160.6 - 162.1
3	36.9 - 38.2 40.5 - 41.8 44.6 - 46.0	14	164.8 - 166.2 169.5 - 171.0 172.4 - 173.7
4	48.5 - 49.8 52.6 - 54.0 56.7 - 58.0	15	176.0 - 177.5 179.8 - 181.0 183.3 - 184.6
5	60.5 - 61.8 64.6 - 65.9 68.5 - 69.8	16	187.5 - 188.6 191.3 - 192.6 195.1 - 196.5
6	72.3 - 73.6 76.3 - 77.6 80.2 - 81.5	17	198.9 - 200.3 202.9 - 204.2 207.0 - 208.4
7	84.2 - 85.5 88.5 - 89.8 92.3 - 93.6	18	211.2 - 212.5 215.1 - 216.4 219.2 - 220.5
8	95.7 - 96.9 99.7 - 101.1 104.0 - 105.1	19	223.4 - 225.0 227.7 - 229.1 231.5 - 233.0
9	107.5 - 108.9 111.0 - 112.3 114.3 - 115.9	20	235.7 - 237.1 240.0 - 241.4 244.1 - 245.7
10	119.0 - 120.7 123.0 - 124.3 127.2 - 128.6	21	248.4 - 249.8 251.4 - 253.0 255.3 - 256.4
11	131.6 - 132.3 134.7 - 136.0 138.4 - 139.6	22	259.1 - 260.3 263.2 - 264.4 267.5 - 268.9

Box	<pre>Intervals (m)</pre>	Box	<pre>Intervals (m)</pre>
23	271.3 - 272.7 275.5 - 276.8 279.5 - 280.6	34	401.0 - 402.5 405.4 - 406.9 411.0 - 412.5
24	283.3 - 284.8 287.4 - 288.8 290.6 - 292.0	35	413.5 - 415.0 417.6 - 419.1 421.9 - 423.4
25	294.7 - 296.2 298.5 - 299.7 302.6 - 304.2	36	426.3 - 427.8 431.1 - 432.6 433.7 - 435.2
26	306.8 - 308.2 312.1 - 313.5 314.7 - 316.1	37	438.3 - 439.8 440.8 - 442.3 446.0 - 447.5
27	318.9 - 320.4 323.0 - 324.2 327.0 - 328.5	38	451.3 - 452.8 454.2 - 455.7 458.2 - 459.7
28	330.6 - 332.1 335.0 - 336.4 339.3 - 346.7	39	463.8 - 465.3 466.6 - 467.1 471.6 - 473.0
29	342.9 - 344.5 347.2 - 348.6 351.5 - 353.0	40	474.3 - 475.8 478.2 - 479.7 483.3 - 484.8
30	355.9 - 357.3 360.0 - 361.3 363.7 - 365.1	41	485.8 - 487.3 491.1 - 492.6 493.9 - 495.4
31	368.0 - 369.4 372.3 - 373.8 376.3 - 377.8		
32	380.3 - 381.8 384.3 - 386.0 388.9 - 390.0		
33	394.0 - 395.5 397.0 - 398.5		

M8-79D HEAT FLOW CONDUCTIVITY SAMPLES (m)

M9-80D PHOTO LOG

Picture #	Box #'s	<pre>Intervals (m)</pre>
1	1-4	127.5 - 142.9
2	5–8	142.9 - 158.3
3	9-12	158.3 - 174.3
4	13-16	174.3 - 190.6
5	17-20	190.6 - 205.8
6	21-24	205.8 - 223.4
7	25-28	223.4 - 239.0
8	29-32	239.0 - 258.1
9	33-36	258.1 - 274.8
10	37-40	274.8 - 291.8
11	41-44	291.8 - 308.4
12	45-48	308.4 - 325.1
13	49-52	325.1 - 342.1
14	53-56	342.1 - 359.7
15	57-60	359.7 - 376.5
16	61-64	376.5 - 393.5
17	65–68	393.5 - 410.1
18	69-72	410.1 - 427.0
19	73–76	427.0 - 444.0
20	77-80	444.0 - 460.5
21	81-84	460.5 - 477.4
22	85–88	477.4 - 494.6 494.6 - 511.5
23	89 - 92 93-96	511.5 - 527.7
24	93 - 96 97 - 100	527.7 - 543.9
25 26	101-104	543.9 - 560.7
27	105-104	560.7 - 577.7
28	109-112	577.7 - 593.9
29	113-116	593.9 - 610.9
30	117-120	610.9 - 627.9
31	121-124	627.9 - 644.5
32	125-128	644.5 - 661.8
33	129-132	661.8 - 677.9
34	133-136	677.9 - 694.8
35	137-140	694.8 - 711.0
36	141-144	711.0 - 728.0
37	145-148	728.0 - 744.7
38	149-152	744.7 - 761.7
39	153-156	761.7 - 777.7
40	157-160	777.7 - 799.8
41	161-164	799.8 - 822.5
42	165-168	822.5 - 845.0
43	169-172	845.0 - 867.5
44	173-176	867.5 - 890.8
45	177-180	890.8 - 913.9

Picture #	Box #'s	Intervals (m)
46	181-184	913.9 - 936.7
47	185-188	936.7 - 959.5
48	189-192	959.5 - 982.6
49	193-196	982.6 - 1004.5
50	197-200	1004.5 - 1026.9
51	201-204	1026.9 - 1050.1
52	205-208	1050.1 - 1074.0
53	209-212	1074.0 - 1097.9
54	213-216	1097.9 - 1121.0
55	217-220	1121.0 - 1142.0

M9-80D CONDENSED

Box	Intervals (m)	Box	Intervals (m)
1	127.5 - 128.9 131.4 - 132.6 135.4 - 136.4	12	262.3 - 263.5 266.4 - 267.8 270.7 - 271.8
2	138.9 - 140.2 142.9 - 144.3 146.9 - 148.2	13	274.8 - 276.1 279.0 - 280.4 283.0 - 284.7
3	150.7 - 152.3 154.8 - 156.2 158.3 - 159.7	14	287.5 - 289.0 291.8 - 293.2 269.0 - 297.4
4	162.2 - 163.6 166.3 - 167.7 170.3 - 171.7	15	300.0 - 301.5 304.1 - 305.8 308.4 - 309.9
5	174.3 - 175.8 179.8 - 181.3 183.1 - 184.5	16	312.5 - 314.0 316.7 - 318.0 320.8 - 322.3
6	186.9 - 188.1 190.6 - 191.9 194.5 - 195.9	17	325.1 - 326.6 329.2 - 330.6 333.6 - 335.0
7	198.1 - 199.6 202.0 - 203.4 205.8 - 207.2	18	337.7 - 339.2 342.1 - 343.5 364.4 - 365.9
8	209.9 - 211.0 215.1 - 216.6 219.5 - 220.9	19	351.1 - 352.6 355.5 - 357.0 359.7 - 361.1
9	223.4 - 224.6 227.1 - 228.5 231.1 - 232.6	20	364.0 - 365.4 368.3 - 369.7 372.5 - 374.0
10	235.0 - 236.5 240.5 - 243.0 244.8 - 246.3	21	376.5 - 378.0 380.8 - 382.3 384.9 - 386.3
11	247.3 - 248.8 251.5 - 255.3 258.1 - 266.4	22	389.2 - 390.6 393.5 - 395.0 397.9 - 399.4

Box	<pre>Intervals (m)</pre>	Box	<pre>Intervals (m)</pre>
23	402.1 - 403.4 405.6 - 407.0 410.1 - 411.6	34	539.9 - 540.7 543.9 - 545.4 548.1 - 549.5
24	414.5 - 416.0 418.7 - 420.1 423.0 - 424.5	35	552.2 - 553.8 556.4 - 557.9 560.7 - 562.1
25	427.0 - 428.5 431.2 - 432.7 435.6 - 437.0	36	565.0 - 566.5 569.2 - 570.6 573.3 - 574.8
	439.8 - 441.2 444.0 - 445.5 448.4 - 449.9	37	577.7 - 579.1 581.6 - 583.0 585.6 - 587.0
27	452.1 - 453.5 456.4 - 457.9 460.5 - 462.0	38	589.8 - 591.2 593.9 - 595.3 598.1 - 599.5
28	464.7 - 466.2 469.1 - 470.5 473.2 - 474.7	39	602.4 - 603.8 606.7 - 608.3 610.9 - 612.4
29	477.4 - 478.8 481.7 - 483.2 486.0 - 487.5	40	615.3 - 616.8 619.7 - 621.1 623.9 - 625.4
30	490.3 - 491.8 494.6 - 496.0 498.8 - 500.0	41	627.9 - 629.3 632.4 - 633.9 636.7 - 637.9
31	502.9 - 504.3 507.2 - 508.7 511.5 - 513.0	42	640.6 - 642.0 644.5 - 646.6 649.2 - 650.7
32	515.8 - 517.2 519.8 - 521.3 523.6 - 525.0	43	653.5 - 654.9 657.6 - 659.0 661.8 - 663.2
33	530.4 - 531.9 531.9 - 533.3 535.9 - 537.4	44	665.7 - 667.2 670.0 - 671.4 674.0 - 675.4

Box	Intervals (m)	Box	<pre>Intervals (m)</pre>
45	677.9 - 679.4 682.0 - 683.5 686.3 - 687.8	56	845.0 - 846.5 850.8 - 852.3 856.2 - 857.7 861.9 - 863.2
46	690.4 - 691.9 694.8 - 696.3 699.0 - 700.5	57	867.5 - 869.0 873.2 - 874.7 879.1 - 880.6
47	702.3 - 703.8 706.7 - 708.2 711.0 - 712.5	58	884.9 - 886.4 890.8 - 892.3
48	715.3 - 716.8 719.4 - 720.9 723.6 - 725.0	30	896.5 - 898.0 902.3 - 903.8 908.2 - 909.7
49	728.0 - 729.5 732.3 - 733.8 736.2 - 737.7	59	913.9 - 915.4 919.7 - 921.2 925.5 - 927.0 931.0 - 932.5
50	740.6 - 742.1 744.7 - 746.0 748.8 - 750.3	60	936.7 - 938.1 942.5 - 943.8 948.1 - 949.6 954.0 - 955.5
51	752.9 - 754.4 757.3 - 758.8 761.7 - 763.2	61	959.5 - 961.0 965.0 - 966.5 971.0 - 972.5
52	765.8 - 766.7 769.7 - 771.2		976.8 - 978.3
53	772.2 - 773.7 777.7 - 779.0 783.0 - 784.5	62	982.6 - 984.1 988.3 - 989.8 993.8 - 995.2 999.6 - 1001.0
54	788.5 - 790.0 794.2 - 795.7 799.8 - 801.3	 63	1004.5 - 1006.0 1010.0 - 1011.5 1015.6 - 1017.1 1021.3 - 1022.8
55	805.4 - 806.9 811.2 - 812.7 817.0 - 818.3 822.5 - 824.0	64	1026.9 - 1028.3 1032.9 - 1034.4 1038.7 - 1040.2 1044.4 - 1045.9
	828.0 - 829.5 833.5 - 835.0 839.2 - 840.7	65	1051.6 - 1053.0 1055.8 - 1057.2 1061.7 - 1063.2 1067.9 - 1069.7

Box	Interv	7a.	ls (m)
66	1074.0	_	1075.4
	1081.9	_	1083.4
	1086.6	_	1088.0
	1092.2	_	1093.7
67	1097.9	_	1099.3
	1107.9	_	1109.3
	1109.3	-	1110.7
	1115.2	-	1116.7
68	1121.0	_	1122.5
	1126.7	-	1128.2
	1132.4	_	1133.9
	1138.1	_	1139.5

M9-80D HEAT FLOW CONDUCTIVITY SAMPLES (m)

(Overburden to 127m)

135	630
150	645
165	660
180	675
195	690
210	705
225	703
240	720
255	750
270	765
285	780
300	· 795
315	810
330	825
345	840
360	855
375	870
390	885
405	900
420	915
435	930
450	945
465	960
480	975
495	990
510	1005
525	1020
540	1035
555	1050
570	1065
585	1080
600	1095
615	1110

M10 PHOTO LOG

Picture #	Box #'s	Intervals (m)
M-10-1	1-4	30.0 - 46.3
M-10-2	5–8	46.3 - 62.5
M-10-3	9-12	62.5 - 78.9
M-10-4	13-16	78.9 - 94.0
M-10-5	17-20	94.0 - 110.7
M-10-6	21-24	110.7 - 127.6
M-10-7	25, 2-4	127.6 - 128.5,136.6-148.6
	Box 1 missing	missing 128.5-136.6
M-10-8	5–8	148.6 - 165.7
M-10-9	9-12	165.7 - 182.1
M-10-10	13-16	182.1 - 198.5
M-10-11	17-20	198.5 - 213.8
M-10-12	21-24	213.8 - 230.5
M-10-13	25–28	230.5 - 246.1
M-10-14	29–32	246.1 - 262.3
M-10-15	33–36	262.3 - 278.3
M-10-16	37–40	278.3 - 295.5
M-10-17	41-44	295.5 - 312.4
M-10-18	45–48	312.4 - 329.3
M-10-19	49-52	329.3 - 347.0
M-10-20	53–56	347.0 - 365.0
M-10-21	57–60	365.0 - 380.7
M-10-22	61–64	380.7 - 398.4
M-10-23	65–68	398.4 - 415.4
M-10-24	69–72	415.4 - 432.6
M-10-25	73–76	432.6 - 449.7
M-10-26	77–80	449.7 - 467.3
M-10-27 M-10-28	81 - 84 85 - 88	467.3 - 484.0
M-10-28 M-10-29	89 – 92	484.0 - 501.6 501.6 - 518.6
M-10-30	93–96	518.6 - 535.5
M-10-31	97–100	535.5 - 552.9
M-10-32	101-104	552.9 - 570.5
M-10-33	105-108	570.5 - 587.8
M-10-34	109-112	3587.8 - 612.5
M-10-35	113-116	612.5 - 634.2
M-10-36	117-120	634.2 - 657.3
M-10-37	121-124	657.3 - 681.3
M-10-38	125-128	681.3 - 702.6
M-10-39	129-132	702.6 - 726.2
M-10-40	133–136	726.2 - 748.7

M10 PHOTO LOG

Picture #	Box #'s	<pre>Intervals (m)</pre>
M-10-41	137-140	748.7 - 767.8
M-10-42	141-144	767 . 8 - 793.6
M-10-43	145-148	793.6 - 816.5
M-10-44	149-152	816.5 - 839.5
M-10-45	153-156	839.5 - 862.7
M-10-46	157-160	862.7 - 885.8
M-10-47	161-164	885.8 - 909.4
M-10-48	165-168	909.4 - 932.2
M-10-49	169-172	932.2 - 956.2
M-10-50	173-176	956.2 - 979.1
M-10-51	177-180	979.1 - 1001.3
M-10-52	181-184	1001.3 - 1025.9
M-10-53	185-188	1025.9 - 1049.4
M-10-54	189-192	1049.4 - 1070.0

M10 CONDENSED

Box #	<pre>Intervals (m)</pre>	Box	# Intervals (m)
1 2	31.3 - 32.8 33.8 - 35.3	14	181.4 - 187.8 182.1 - 183.6 190.5 - 192.0
3	38.3 - 39.3 42.5 - 43.5 46.3 - 47.6	15	197.0 - 198.5 201.2 - 202.6
	50.2 - 51.5 54.4 - 55.9	16	203.9 - 205.0 208.6 - 209.9 212.7 - 213.8
4	58.5 - 59.9 62.5 - 63.9 66.8 - 68.3	17	216.9 - 218.5 218.5 - 219.9
5	73.9 - 75.1 76.3 - 77.0 78.9 - 80.4	18	222.6 - 224.0 226.8 - 228.1 230.5 - 231.7
6°	83.0 - 84.0 86.3 - 87.5		230.3 - 231.7 237.2 - 238.5 240.8 - 242.1
7	89.9 - 91.1 94.0 - 95.5	19	243.5 - 244.9 246.1 - 247.1 252.5 - 254.0
8	98.4 - 99.9 102.2 - 103.6 106.1 - 107.6	20	256.7 - 258.3 261.0 - 262.3
0	112.0 - 113.5 117.5 - 118.5	21	264.0 - 265.0 268.8 - 270.2
9	118.8 - 120.3 123.0 - 124.8 127.6 - 128.5	22	273.0 - 274.3 274.3 - 275.8 279.7 - 281.2
10	132.5 - 134.0 139.0 - 140.5	22	283.9 - 285.4 288.5 - 289.9
11	140.5 - 142.0 145.9 - 147.4	23	292.5 - 291.0 295.5 - 297.0 302.3 - 303.8
1.2	148.6 - 150.1 152.6 - 154.0	24	306.7 - 308.2 308.2 - 309.7
12	156.8 - 158.2 160.9 - 162.4 165.3 - 166.8	25	312.4 - 313.9 318.5 - 319.8
13	169.2 - 170.7 174.7 - 176.0		321.2 - 322.7 326.3 - 227.8
	180.6 - 182.1	26	329.3 - 331.0 336.7 - 338.2 341.0 - 342.5

M10 CONDENSED

Box #	<pre>Intervals (m)</pre>	<u>Box #</u>	<pre>Intervals (m)</pre>
27	342.5 - 344.2 349.7 - 351.1 351.1 - 353.0	41	522.8 - 524.2 529.9 - 531.4 531.4 - 532.9
28	358.9 - 360.1 361.6 - 363.1 365.0 - 366.5	42	538.7 - 540.1 540.1 - 541.7 544.4 - 545.9
29	371.5 - 372.5 373.9 - 373.3 376.5 - 378.0	43	551.2 - 552.7 555.7 - 557.2 557.2 - 558.7
30	380.7 - 382.2 385.4 - 386.5 391.0 - 392.7	44	361.5 - 563.0 566.0 - 567.5 573.5 - 574.9
31	395.6 - 397.1 398.4 - 400.0 405.5 - 407.0	45	574.9 - 576.4 579.1 - 580.7 583.7 - 584.9
32	409.8 - 411.2 413.9 - 415.4 418.3 - 419.7	46	587.8 - 589.8 594.3 - 595.8 601.0 - 602.5 604.8 - 605.8
33	422.7 - 424.2 424.2 - 425.7 431.1 - 432.6	47	615.5 - 617.0 621.6 - 622.8 622.8 - 624.2
34	432.6 - 434.1 437.0 - 438.5 441.4 - 442.9	48	628.5 - 629.7 634.2 - 635.7
35	448.2 - 449.2 449.7 - 451.0 453.9 - 455.3		644.3 - 645.8 648.5 - 650.0 655.8 - 657.3
36	458.4 - 459.9 465.8 - 467.3 469.9 - 471.4	49	657.3 - 658.8 667.6 - 668.4 673.4 - 674.4 677.4 - 678.9
37	473.8 - 475.3 475.5 - 477.0 482.5 - 484.0	50	680.3 - 681.8 686.0 - 687.5 693.6 - 695.1
38	486.9 - 488.4 491.1 - 492.6 492.6 - 497.2	51	697.9 - 699.4 703.6 - 705.1 709.4 - 710.9
39	497.2 - 498.7 504.4 - 505.9 505.8 - 507.3	50	715.2 - 716.7 721.8 - 722.3
40	511.7 - 513.2 517.3 - 518.8 521.3 - 522.8	52	726.2 - 727.7 732.3 - 733.8 738.5 - 740.0 743.0 - 744.5

M10 CONDENSED

Box #	Intervals (m)	Box #	Intervals (m)
53	749.5 - 751.0 754.8 - 755.3 759.8 - 761.3 767.2 - 768.7	63	979.1 - 980.6 984.8 - 986.3 990.5 - 992.0 996.2 - 997.4
54	771.0 - 722.5 776.0 - 777.5 781.9 - 783.4 787.5 - 789.3	64	1001.3 - 1003.3 1010.0 - 1011.5 1016.0 - 1017.5 1020.4 - 1021.9
55	793.5 - 795.0 799.2 - 800.5 804.5 - 806.0 810.5 - 812.1	65	1027.2 - 1028.7 1033.0 - 1034.5 1037.4 - 1038.9 1046.2 - 1047.7
56	817.9 - 819.4 822.4 - 823.1 829.5 - 831.0 833.8 - 835.2	66	1049.4 - 1050.9 1055.0 - 1056.5 1060.3 - 1061.8 1066.1 - 1067.6
57	840.8 - 842.3 845.2 - 846.5 851.0 - 852.5 856.8 - 858.3		
58	862.7 - 864.1 871.7 - 873.0 876.0 - 877.4 880.1 - 881.6		
59	885.8 - 887.3 891.5 - 893.0 897.0 - 899.0 903.3 - 904.7		
60	909.4 - 910.8 916.5 - 918.0 920.5 - 922.0 927.6 - 929.1		
61	932.2 - 933.7 938.3 - 939.8 945.5 - 947.0 950.3 - 951.8		
62	956.2 - 957.7 961.8 - 963.3 967.6 - 969.0 974.0 - 975.5		

M10 HEAT FLOW CONDUCTIVITY SAMPLES (m)

555
570
585
600
615
630
645
660
675
690
705
720
735
750
765
780
795
810
825
840
855
870
885
900
915
930
945
960
985
1000
1015
1030
1045
1060

M11-80 D PHOTO LOG

Picture #	Box #'s	<u>Intervals (m)</u>
1	1-4	16.5 - 32.7
2	5–8	32.7 - 48.2
3	9-12	48.2 - 64.9
4	13-16	64.9 - 81.0
5	17-20	81.0 - 96.1
6	21-24	96.1 - 112.2
7	25-28	112.2 - 128.0
8	29-32	128.0 - 144.0
9	33-36	144.8 - 161.0
10	37-40	161.0 - 178.2
11	41-44	178.2 - 193.7
12	45-48	193.7 - 210.7
13	49-52	210.7 - 227.4
14	53-56	227.4 - 243.2
15	57-60	243.2 - 259.2
16	61-64	259.2 - 278.2
17	65–68	278.2 - 301.5
18	69-72	301.5 - 324.1
19	73–76	324.1 - 347.2
20	77-80	347.2 - 370.1
21	81-84	370.1 - 393.0
22	85–88	393.0 - 415.9
23	89-92	415.9 - 438.5
24	93-96	438.5 - 461.3
25	97-100	461.3 - 484.3
26	101-104	484.3 - 507.1
27	105-108	507.1 - 531.2
28	109-112	531.2 - 554.0
29	113	554.0 - 559.4

M11-80D CONDENSED

Box	<u>Intervals (m)</u>	Box	<pre>Intervals (m)</pre>
1	19.5 - 20.9 20.9 - 22.3 24.6 - 26.1	12	148.9 - 150.4 153.2 - 154.7 157.3 - 158.8
2	28.6 - 29.8 32.7 - 34.1 36.4 - 37.9	13	161.0 - 162.5 165.1 - 166.5 169.3 - 170.7
3	40.4 - 41.8 44.6 - 46.0 48.2 - 49.7	14	173.6 - 175.4 178.2 - 179.7 181.8 - 183.2
4	52.5 - 53.9 56.6 - 58.1 60.7 - 62.2	15	185.5 - 187.0 189.3 - 190.8 193.7 - 195.0
5	64.8 - 66.3 69.1 - 70.6 73.3 - 74.8	16	198.0 - 199.5 202.3 - 203.8 206.5 - 208.0
6	77.3 - 78.8 81.0 - 82.5 85.1 - 86.6	17	210.7 - 212.2 215.0 - 216.5 219.0 - 220.5
7	90.2 - 91.6 93.1 - 94.5 96.1 - 97.6	18	223.3 - 224.8 227.4 - 228.9 231.4 - 232.6
8	100.5 - 101.9 104.4 - 105.9 108.1 - 109.5	19	235.3 - 236.8 240.6 - 241.9 243.2 - 244.1
9	112.2 - 113.7 118.6 - 120.0 120.0 - 123.3	20	247.4 - 248.9 251.5 - 253.0 255.3 - 256.7
10	124.4 - 125.8 130.7 - 132.2 132.2 - 133.4	21	260.5 - 262.0 262.5 - 264.0 267.0 - 268.5
11	138.0 - 139.3 140.7 - 142.2 144.8 - 146.3	22	272.7 - 274.2 282.6 - 284.1 284.1 - 285.6 290.0 - 291.5

Box	<pre>Intervals (m)</pre>	Box	<pre>Intervals (m)</pre>
23	295.8 - 297.3 301.5 - 303.0 307.2 - 308.7 312.8 - 314.2	32	511.5 - 513.0 518.0 - 519.5 519.5 - 521.0 527.3 - 528.8
24	318.4 - 319.9 324.1 - 325.6 329.9 - 331.4 335.7 - 337.2	33	534.0 - 535.5 541.3 - 542.8 542.6 - 544.1 548.3 - 549.8
25	341.4 - 342.9 347.2 - 348.7 352.8 - 354.3 358.6 - 360.1	34	554.0 - 555.5
26	370.1 - 371.6 375.5 - 377.0 381.5 - 383.0 384.0 - 385.5		
27	387.3 - 388.7 393.0 - 394.5 398.5 - 400.0 404.2 - 405.7		
28	410.0 - 411.5 415.9 - 417.4 421.2 - 422.7 431.3 - 432.7		
29	432.7 - 434.2 438.5 - 440.0 444.4 - 445.8 450.0 - 451.5		
30	455.5 - 457.0 461.3 - 462.8 467.2 - 468.7 472.9 - 474.4		
31	478.7 - 480.2 484.3 - 485.3 490.1 - 491.5 495.7 - 497.2		

M11-80D HEAT FLOW CONDUCTIVITY SAMPLES (m)

M-12 PHOTO LOG

Picture #	Box #'s	<pre>Intervals (m)</pre>	
1	1-4	11.5 - 29.5	
2	5–8	29.5 - 45.8	
3	9-12	45.8 - 62.3	
4	13-16	62.3 - 78.8	
5	17-20	78.8 - 95.8	
6	21-24	95.8 - 112.8	
7	25-28	112.8 - 129.8	
8	29-32	129.8 - 146.4	
9	33–36	146.4 - 162.8	
10	37-40	162.8 - 175.3	
- 11	41-44	175.3 - 195.8	
12	45-48	195.8 - 208.0	Box 46 missing
13	49-52	208.0 - 224.8	
14	53-56	224.8 - 241.9	
15	57-60	241.9 - 258.5	
16	61-64	258.5 - 275.6	
17	65–68	275.6 - 292.9	
18	69-72	292.9 - 309.8	Box 67 & 70 missing
19	73-76	309.8 - 327.1	
20	77-80	327.1 - 343.8	
21	81-84	343.8 - 360.6	
22	85-88	360.6 - 377.2	
23	89-92	377.2 - 398.7	
24	93-96	398.7 - 421.7	
25	97-100	421.7 - 444.9	
26	101-104	444.9 - 468.2	
27	105-108	468.2 - 491.0	
28	109-112	491.0 - 513.4	
29	113-116	513.4 - 536.8	
30	117-120	536.8 - 559.3	
31	121-124	559.3 - 581.8	
32	125-128	581.8 - 605.0	
	•		

M-12 CONDENSED

Box #	Intervals (m)	Box #	Intervals (m)
1	11.5 - 13.0 17.5 - 19.0 21.6 - 22.9	12	150.3 - 151.5 154.4 - 155.5 158.5 - 159.8
2	25.6 - 27.1 29.5 - 31.0 33.8 - 35.3	13	162.8 - 164.3 167.0 - 168.5 171.1 - 172.6
3	37.8 - 39.8 41.8 - 43.3 45.8 - 47.3	14	175.3 - 176.8 179.4 - 180.9 183.5 - 185.0
4	50.0 - 51.5 54.3 - 55.8 58.6 - 59.7	15	187.6 - 189.1 191.5 - 193.0 195.8 - 197.3
5	62.3 - 63.8 66.2 - 67.3 70.5 - 72.0	16	200.0 - 201.5 204.0 - 205.5
6	74.5 - 76.0 78.8 - 80.4 83.2 - 84.7	17	208.0 - 209.5 212.2 - 213.7 216.3 - 217.8
7	87.4 - 88.9 91.7 - 93.2 95.8 - 97.3	18	220.5 - 222.0 224.8 - 226.3 229.0 - 230.5
8	100.0 - 101.5 104.3 - 105.8 108.5 - 110.0	19	233.3 - 234.8 237.6 - 338.1 241.9 - 243.4
9	112.8 - 114.3 116.9 - 118.3 121.3 - 122.6	20	246.1 - 247.6 250.2 - 251.7 254.4 - 255.8
10	125.4 - 126.9 129.8 - 131.3 134.0 - 135.5	21	258.5 - 260.0 262.7 - 264.2 267.1 - 268.6
11	138.1 - 139.6 142.4 - 144.0 146.4 - 147.8	22	271.4 - 272.9 275.6 - 277.1 280.0 - 281.5

Box #	Intervals (m)	Box #	Intervals (m)
23	284.3 - 285.9 288.6 - 290.1	35	485.5 - 487.0 491.0 - 492.5 496.1 - 497.6
24	301.0 - 302.5 305.5 - 307.0		502.0 - 503.5
25	309.8 - 311.2 314.1 - 315.6 318.5 - 320.0	36	507.8 - 509.2 513.4 - 514.8 519.2 - 520.7 525.1 - 526.6
26	322.8 - 324.3 327.1 - 328.6 331.1 - 332.4	37	531.1 - 532.6 536.8 - 538.3 542.5 - 544.0 548.0 - 549.4
27	335.4 - 336.9 339.6 - 341.1 343.8 - 345.3	38	553.7 - 555.2 559.3 - 560.7 565.0 - 566.5
28	348.0 - 349.5 352.3 - 353.7 356.3 - 357.8	39	570.7 - 572.2 576.4 - 577.8
29	360.6 - 362.1 364.7 - 366.2 369.0 - 370.5		581.8 - 583.3 587.3 - 588.8 593.2 - 594.7
30	376.0 - 377.2 377.2 - 378.7 381.5 - 383.0 387.1 - 388.6	40	601.9 - 603.4
31	392.9 - 394.4 398.7 - 400.2 404.5 - 406.0 410.2 - 411.7		
32	416.0 - 417.5 421.7 - 423.2 427.5 - 429.0 433.3 - 434.8		
33	439.2 - 440.7 444.9 - 446.4 450.7 - 452.2 456.5 - 458.0		
34	462.4 - 463.8 468.2 - 469.7 474.0 - 475.5 479.7 - 481.2		

M-12 HEAT FLOW CONDUCTIVITY SAMPLES (m)

M13 PHOTO LOG

Picture #	Box #'s	<pre>Intervals (m)</pre>
M-13-1	1-4	25 - 41.5
M-13-2	5–8	41.5 - 58.3
M-13-3	9-12	58.3 - 77.0
M-13-4	13-16	77.0 - 93.2
M-13-5	17-20	93.2 - 111.6
M-13-6	21-24	111.6 - 127.9
M-13-7	25-28	127.9 - 143.7
M-13-8	29-32	143.7 - 160.0
M-13-9	33-36	160.0 - 175.6
M-13-10	37-40	175.6 - 191.4
M-13-11	41-44	191.4 - 207.2
M-13-12	45-48	207.2 - 222.8
M-13-13	49-52	222.8 - 239.0
M-13-14	53-56	239.0 - 254.6
M-13-15	57 – 60	254.6 - 270.4
M-13-16	61-64	270.4 - 286.7
M-13-17	65 - 68	286.7 - 302.5
M-13-18	69-72	302.5 - 319.0
M-13-19	73-76	319.0 - 335.3
M-13-20	77-80	335.3 - 351.9
M-13-21	81-84	351.9 - 368.4
M-13-22	85 – 88	368.4 - 385.0
M-13-23	89-92	385.0 - 401.3
M-13-24	93-96	401.3 - 422.5
M-13-25	97-100	422.5 - 444.7
M-13-26	101-104	444.7 - 467.5
M-13-27	105-108	467.5 - 490.5
M-13-28	109-112	490.5 - 513.3
M-13-29	113-116	513.3 - 536.2
M-13-30	117-120	536.2 - 559.4
M-13-31	121-124	559.4 - 581.9
M-13-32	125-128	581.9 - 599.5

M13 CONDENSED

Box #	Intervals (m)	Box #	Intervals (m)
1	27.1 - 28.3 29.7 - 31.0 34.0 - 35.3	14	187.5 - 189.0 191.4 - 192.9 195.3 - 196.8
2	38.1 - 40.2 41.5 - 43.1 47.8 - 50.0	15	199.0 - 200.5 203.0 - 204.5 207.2 - 208.7
3	53.0 - 54.5 57.0 - 58.8 58.8 - 59.7	16	210.9 - 212.4 215.0 - 216.5 218.6 - 220.1
4	62.5 - 64.7 69.8 - 71.3 72.7 - 74.8	17	222.8 - 224.3 226.5 - 228.0 230.5 - 232.0
5	80.3 - 81.0 83.7 - 85.0 87.8 - 89.0	18	235.0 - 236.5 239.0 - 240.5 242.7 - 244.2
6	92.0 - 93.2 96.5 - 98.0 101.0 - 102.6	19	247.1 - 248.6 251.3 - 252.8 254.6 - 256.1
7	106.2 - 107.5 107.5 - 109.0 111.6 - 113.0	20	258.9 - 260.4 262.5 - 264.0 266.4 - 267.9
8	118.0 - 119.6 122.5 - 124.0 124.0 - 125.2	21	270.4 - 271.9 274.2 - 275.7 278.2 - 277.7
9	127.9 - 129.4 131.8 - 133.3 136.0 - 137.5	22	282.5 - 284.0 286.7 - 288.2 290.8 - 292.3
10	140.0 - 141.5 143.7 - 145.2 147.9 - 149.4	23	294.1 - 295.6 298.6 - 300.1 302.5 - 304.0
11	151.8 - 153.3 155.9 - 157.4 160.0 - 161.5	24	306.5 - 308.0 310.6 - 312.1 314.7 - 316.2
12	164.0 - 165.5 167.7 - 169.2 171.8 - 173.3	25	319.0 - 320.5 323.1 - 324.6 327.4 - 328.9
13	175.6 - 177.1 179.8 - 181.3 183.6 - 185.1	26	331.4 - 332.9 335.3 - 336.8 339.4 - 340.9

M13 CONDENSED

Box #	<pre>Intervals (m)</pre>	Box #	Intervals (m)
27	343.6 - 344.7 347.6 - 349.0 351.9 - 353.3	34	450.2 - 452.0 456.0 - 457.8 461.6 - 462.8 467.5 - 468.6
28	356.0 - 357.7 360.0 - 361.5 364.2 - 365.5	35	473.3 - 474.3 479.0 - 480.2
29	368.4 - 369.8 372.6 - 373.5		485.0 - 486.1 490.5 - 491.8
	376.6 - 377.8	36	496.1 - 497.5 501.8 - 503.3
30	380.7 - 382.2 385.0 - 386.3 389.1 - 390.6		507.5 - 509.1 513.3 - 515.0
31	393.0 - 394.3 397.0 - 398.4 401.3 - 403.0	37	519.0 - 520.5 524.7 - 526.2 530.5 - 532.0 536.2 - 537.7
32	405.0 - 406.3 411.0 - 412.9 416.7 - 417.9 422.5 - 423.6	38	542.0 - 543.5 547.8 - 549.3 553.7 - 555.2 559.4 - 560.9
33	428.2 - 429.6 433.7 - 434.9 439.2 - 440.5 444.7 - 446.3	39	564.0 - 566.4 570.5 - 572.0 576.1 - 577.6 581.9 - 583.4
		40	587.5 - 589.0 593.3 - 594.8 599.1 - 599.5

M13 HEAT FLOW CONDUCTIVITY SAMPLES (m)

M14 PHOTO LOG

Picture #	Box #'s	Intervals (m)
M-14-1	1-4	10.0 - 25.9
M-14-2	5–8	25.9 - 41.1
M-14-3	9-12	41.1 - 56.9
M-14-4	13-16	56.9 - 71.8
M-14-5	17-20	71.8 - 88.6
M-14-6	21-24	88.6 - 105.3
M-14-7	25–28	105.3 - 121.8
M-14-8	29-32	121.8 - 138.6
M-14-9	33–36	138.6 - 155.3
M-14-10	37–40	155.3 - 172.5
M-14-11	41-44	172.5 - 189.1
M-14-12	45-47, 49	189.1 - 201.8, 205.4 - 209.5
M-14-13	48, 50-52	201.2 - 205.4, 209.5 - 222.1
M-14-14	53-56	222.1 - 240.5
M-14-15	57–60	240.5 - 255.8
M-14-16	61-64	255.8 - 272.6
M-14-17	65–68	272.6 - 288.7
M-14-18	69-72	288.7 - 304.8
M-14-19	73 - 76	304.8 - 321.0
M-14-20	77–80	321.0 - 342.3
M-14-21	81-84	342.3 - 364.9
M-14-22	85-88	364.9 - 387.7
M-14-23	89-92	387.7 - 404.5
M-14-24	93-96	404.5 - 432.9
M-14-25	97-100	432.9 - 455.5
M-14-26	101-104	455.5 - 478.2
M-14-27	105-108	478.2 - 500.4
M-14-28	109-112	500.4 - 523.5
M-14-29	113-116	523.5 - 546.5
M-14-30	117-120	546.5 - 569.5
M-14-31	121-122	569.5 - 578.5

M14 CONDENSED

Box #	Intervals (m)		Box #	Intervals (m)
1	10.0 - 11.4 15.0 - 16.5 17.7 - 19.2		14	168.0 - 169.6 175.3 - 176.8 176.8 - 178.3
2	21.7 - 23.2 25.9 - 27.4 30.0 - 31.0	,	15	180.8 - 182.3 184.9 - 186.3 189.1 - 190.5
3	34.0 - 35.5 38.2 - 38.7 42.5 - 43.8		16	195.8 - 197.3 197.3 - 198.5 202.7 - 204.0
4	45.0 - 46.2 50.4 - 51.8 52.8 - 53.9		17	203.4 - 206.9 209.5 - 210.8 213.7 - 215.2
5	56.8 - 58.0 60.5 - 61.8 65.0 - 66.4		18	218.2 - 219.5 223.5 - 225.0 227.5 - 229.0
6	67.8 - 68.3 71.8 - 73.3 76.1 - 77.1		19	230.3 - 233.6 236.4 - 237.9 240.5 - 242.0
7	80.3 - 81.8 84.5 - 85.9 88.6 - 90.1		20	245.7 - 247.2 248.4 - 249.9 252.5 - 254.0
8	93.8 - 95.3 99.6 - 101.0 101.1 - 102.4		21	258.0 - 259.2 260.5 - 262.0 264.4 - 265.9
9	105.3 - 106.9 109.7 - 111.2 113.7 - 114.8		22	268.4 - 269.9 272.2 - 273.6 276.4 - 277.9
10	117.5 - 119.0 121.8 - 123.3 126.0 - 127.5		23	280.5 - 281.7 284.5 - 285.9 290.2 - 291.2
11	131.5 - 133.0 135.7 - 137.2 138.6 - 140.1		24	292.7 - 293.8 296.8 - 298.3 302.2 - 303.5
12	142.9 - 144.2 146.8 - 148.5 151.2 - 153.0		25	304.8 - 305.7 308.3 - 309.5 312.0 - 313.0
13	155.1 - 156.6 160.9 - 162.3 165.2 - 166.7		26	315.9 - 317.3 322.0 - 323.5 326.3 - 327.8 332.7 - 334.2

(5)

. . .

M14 CONDENSED

Box #	Intervals (m)	Box #	Intervals (m)
27	336.9 - 338.3 342.3 - 343.8 347.8 - 349.3 353.6 - 355.1	36	540.8 - 542.3 546.6 - 548.1 552.5 - 554.0 558.2 - 559.7
28	360.3 - 361.8 366.0 - 367.5 372.0 - 373.5 380.3 - 381.8	37	563.9 - 565.4 569.5 - 571.0 575.5 - 577.0
29	381.8 - 383.3 387.7 - 389.2 393.6 - 395.1 399.1 - 400.6		
30	404.6 - 406.1 410.4 - 411.9 416.2 - 417.7 421.7 - 423.2		
31	429.9 - 431.4 435.7 - 437.2 438.5 - 440.0 445.8 - 447.2		
32	450.1 - 451.6 455.5 - 457.0 461.5 - 463.0 466.7 - 467.8		
33	472.3 - 473.8 482.2 - 483.6 485.0 - 486.5 489.2 - 490.7		•
34	494.8 - 495.8 500.3 - 501.4 506.2 - 507.7 512.0 - 513.5		
35	517.5 - 519.0 523.2 - 524.7 529.0 - 530.5 534.9 - 536.5		

M14 HEAT FLOW CONDUCTIVITY SAMPLES (m)

as per core boxes

L1-78D

L2-80D

L3-80D

L4-81D & 82D Extension Photo Log

L5-81D

L6-81D

L7-82D

L8-82D

L1-78D PHOTO LOG

Picture #	Box's	Intervals (ft)
1	1-4	153 - 372
2	5–8	372 - 436.5
3	9-12	436.5 - 485.5
4	13-16	485.5 - 535.0
5	17-20	535.0 - 588.0
6	21-24	588.0 - 643.0
7	25-28	643.0 - 698.0
8	29-32	698.0 - 753.0
9	33-36	753.0 - 826.0
10	37–40	826.0 - 907.0
11	41-44	907.0 - 983.0
12	45-48	983.0 - 1053.0
13	49-52	1053.0 - 1124.0
14	53-56	1124.0 - 1198.0
15	57-60	1198.0 - 1268.0
16	61-64	1268.0 - 1344.0
17	65–68	1344.0 - 1415.0
18	69-72	1415.0 - 1487.0
19	73–76	1487.0 - 1570.0
20	77-80	1570.0 - 1641.0
21	81-84	1641.0 - 1713.0
22	85-88	1713.0 - 1786.0
23	89-92	1786.0 - 1858.0
24	93-95	1858.0 - 1920.0
25	96-98	1920.0 - 1980.0

L1-78D CONDENSED

Box #	Intervals (ft)	Box #	Intervals (ft)
1	153 - 158 172 - 178 228 - 354	12	771 - 776 790 - 795 803 - 808 834 - 839
2	359 - 364 371 - 376 395 - 400	13	853 - 858 870 - 875 889 - 894
3	407 - 412 424 - 429 437 - 441	14	906 - 911 927 - 932
4	456 - 461 474 - 479 473 - 478		946 - 950 964 - 969 982 - 987
. 5	483 - 489 495 - 500 510 - 515	15	1001 - 1006 1020 - 1026 1035 - 1040 1053 - 1058
6	522 - 527 535 - 540 548 - 553	16	1070 - 1075 1086 - 1091 1104 - 1109 1123 - 1128
7	560 - 565 575 - 579 588 - 593	17	1141 - 1146 1161 - 1166
8	602 - 607 615 - 620 629 - 634	18	1180 - 1185 1992 - 1997 1212 - 1217
9	643 - 648 656 - 661 670 - 675	10	1231 - 1236 1251 - 1256 1267 - 1272
10	683 - 688 697 - 702 710 - 715	19	1286 - 1291 1306 - 1311 1323 - 1328 1341 - 1346
11	725 - 730 740 - 744 753 - 758	20	1358 - 1363 1378 - 1383 1396 - 1401 1413 - 1418

Box #	Intervals (ft)
21	1430 - 1435 1451 - 1456 1470 - 1474 1494 - 1498
22	1513 - 1518 1533 - 1538 1550 - 1555 1574 - 1579
23	1586 - 1591 1605 - 1610 1623 - 1628 1641 - 1646
24	1658 - 1663 1676 - 1681 1694 - 1699 1711 - 1716
25	1730 - 1735 1749 - 1754 1768 - 1773 1786 - 1791
26	1804 - 1809 1822 - 1827 1838 - 1842 1876 - 1881
27	1884 - 1888 1903 - 1908 1922 - 1926 1958 - 1962
28	1962 - 1966

L1-78D HEAT FLOW CONDUCTIVITY SAMPLES (ft)

L2 PHOTO LOG

Picture #	Box #'s	Interval (feet)
1	1-4	33 - 105
2	5–8	105 - 175
3	9-12	175 - 246
4	13-16	246 - 338
5	17-20	338 - 421
6	21-24	421 - 488
7	25-28	488 - 559
8	29-32	559 - 627
9	33-36	627 - 697
10	37-40	697 - 767
11	41-44	767 - 833
12	45-48	833 - 897
13	49-52	897 – 968
14	53-56	968 - 1042
15	57-60	1042 - 1115
16	61-64	1115 - 1188
17	65–68	1188 - 1258
18	69-72	1258 - 1327
19	73-76	1327 - 1394
20	77–80	1394 - 1461
21	81-84	1461 - 1525
22	85–88	1525 - 1591
23	89-92	1591 - 1662
24	93–96	1662 - 1730
25	97-100	1730 - 1796
26	101-104	1796 - 1859
27	105-108	1859 - 1923
28	109-110	1923 - 1953

L-2 CONDENSED (feet)

Box	Interval	Box	Interval
1	33 - 38 50 - 55 67 - 72 87.5 - 92.5	10	697 - 702 715 - 720 732 - 737 748 - 753
2	105 - 110 123 - 128 141 - 146 167 - 172	11	767 - 772 783 - 788 798 - 803 815 - 820
3	175.5 - 180.5 191 - 196 210 - 215 228.8 - 233.8	12	833 - 838 850 - 855 864 - 869 880 - 885
4	246.2 - 251.2 269 - 274 282 - 287 305 - 310	13	897 - 902 922 - 927 932 - 937 950 - 955
5	338 - 343 369 - 374 395 - 400 406.5 - 411.5	14	968 - 972 986 - 990 1004 - 1009 1023 - 1028
6	421.5 - 426.5 436 - 441 452.2 - 457.2 471 - 476	15	1042 - 1047 1060 - 1065 1079 - 1084 1098 - 1103
7	488.5 - 493.5 506 - 511 522.5 - 527.5 537 - 542	16	1115 - 1120 1126 - 1131 1152 - 1157 1170 - 1175
8	559.5 - 564.5 577 - 582 594.2 - 599.2 610 - 615	17	1188 - 1193 1206 - 1211 1225 - 1230 1241 - 1246
9	627.5 - 632.5 646.5 - 651.5 664.5 - 669.5 679.2 - 684.2	18	1258 - 1263 1275 - 1280 1294 - 1299 1312 - 1317

L2 CONDENSED Page 2

Box	Interval
19	1327 - 1332 1343 - 1348 1360 - 1365 1379 - 1384
20	1394 - 1399 1411 - 1416 1427 - 1432 1444 - 1449
21	1461 - 1466 1480 - 1485 1495 - 1500 1509 - 1514
22	1525 - 1530 1540 - 1545 1554 - 1559 1575 - 1580
23	1591 - 1596 1611 - 1616 1626 - 1631 1645 - 1650
24	1662 - 1667 1678 - 1683 1696 - 1701 1714 - 1719
25	1730 - 1735 1748 - 1753 1764 - 1769 1779 - 1784
26	1796 - 1801 1812 - 1817 1828 - 1832 1844 - 1849

L2 HEAT FLOW CONDUCTIVITY SAMPLES

L3 PHOTO LOG

1980 Drilling depths recorded in feet; Boxes 1 - 35, interval 252 - 840

Picture #	Box #'s	Intervals (ft)
1	1 4	252.0 204.5
1	1-4	252.0 - 294.5
2	5–8	294.5 - 376.5
3	9-12	376.5 - 427.0
4	13-16	427.0 - 524.5
5	17-20	524.5 - 590.5
6	21-24	590.5 - 658.0
7	25-28	658.0 - 730.0
8	29-32	730.0 - 798.0
9	33-35	798.0 - 840.0

1981 Drilling depths recorded in metres

Picture #	Box #'s	<pre>Intervals (m)</pre>
10	1-4	259.0 - 280.5
11	5–8	280.5 - 300.3
12	9-12	300.3 - 321.7
13	13-16	321.7 - 341.9
14	17-20	341.9 - 362.7
15	21-24	362.7 - 382.2
16	25–28	382.2 - 404.4
17	29–32	404.4 - 425.0
18	33–36	425.0 - 447.2
19	37–40	447.2 - 469.4
20	41-44	469.4 - 491.2
21	45-48	491.2 - 513.2
22	49-52	513.2 - 534.3
23	53–56	534.3 - 556.7
24	57–60	556.7 - 577.8
25	61-64	577.8 - 597.6
26	65–68	597.6 - 615.5
27	69-72	615.5 - 643.1
28	73–76	643.1 - 671.2
29	77–80	671.2 - 698.3
30	81-84	698.3 - 727.3
31	85-88	727.3 - 754.6
32	89-92	754.6 - 784.1
33	93-96	784.1 - 813.3
34	97-100	813.3 - 840.5
35	101-104	840.5 - 868.5
36	105-108	868.5 - 897.3
37	109-112	897.3 - 924.6
38	113-116	924.6 - 947.1
39	117-120	947.1 - 971.3
40	121-124	971.3 - 1000.0
41	125-126	1000.0 - 1010.0

L3 CONDENSED

Box #	Intervals (ft)	<u>Box #</u>	Intervals (m)
1	252.0 - 260.0 260.0 - 265.0 267.0 - 272.0	ll cont'd	254.0 - 255.5 263.6 - 265.0 267.0 - 268.3
2	277.0 - 282.0 289.0 - 294.5 294.5 - 299.5	12	274.0 - 277.0 280.5 - 282.0 285.2 - 286.7 290.0 - 291.5
3	307.0 - 312.0 351.5 - 357.0 367.0 - 372.0	13	298.0 - 299.3 302.7 - 304.2 305.7 - 307.2
4	376.5 - 381.5 389.0 - 394.0 401.0 - 405.0	14	311.0 - 312.5 317.0 - 318.0
5	418.5 - 423.5 436.0 - 441.5 441.5 - 446.5		321.7 - 323.0 329.2 - 330.7 332.0 - 333.5
6	487.0 - 492.0 507.0 - 512.0 524.0 - 529.0	15	339.7 - 341.2 344.5 - 345.9 347.2 - 348.7 352.8 - 354.3
7	542.0 - 547.0 557.0 - 562.0 573.0 - 578.0 590.0 - 595.0	16	360.7 - 362.0 363.7 - 365.2 367.5 - 369.0 372.7 - 374.2
8	612.0 - 617.0 624.0 - 629.0 650.0 - 655.0 658.0 - 663.0	17	379.2 - 379.7 383.8 - 385.3 389.7 - 391.2 393.6 - 395.1
9	676.0 - 681.0 695.0 - 700.0 713.0 - 718.0 730.0 - 735.0	18	399.0 - 400.5 404.4 - 405.9 410.8 - 412.3 415.1 - 416.4
10	747.0 - 752.0 764.5 - 770.0 781.0 - 786.0 798.0 - 803.0	19	420.8 - 422.0 425.0 - 426.4 429.5 - 430.7 435.4 - 436.8
11	817.0 - 823.0 835.5 - 840.0	20	441.3 - 442.8 447.2 - 448.7 456.5 - 458.0 458.0 - 459.5

L3 CONDENSED

Box #	Intervals (m)		<u>Box #</u>	Intervals (m)
21	463.9 - 465.0 469.4 - 470.9 474.9 - 476.4 480.0 - 481.5		31	705.9 - 707.4 713.3 - 714.8 720.0 - 721.5 727.3 - 728.9 734.3 - 735.8
22	485.3 - 486.8 491.2 - 492.3 496.7 - 498.1 502.3 - 503.8		32	740.6 - 742.1 747.7 - 749.3 754.8 - 756.3
23	508.0 - 509.5 513.2 - 514.4 518.5 - 520.5 523.9 - 525.2		33	762.4 - 736.9 769.4 - 770.9 778.5 - 780.0 784.1 - 785.6
24	532.9 - 534.3 534.3 - 535.7 540.0 - 541.4			790.8 - 792.3 798.5 - 800.0 805.8 - 807.3
25	545.4 - 546.9 551.1 - 552.6 556.7 - 558.5 561.4 - 562.8 567.3 - 568.8		34	814.7 - 816.2 821.6 - 823.0 828.0 - 829.4 833.6 - 835.0 840.5 - 841.9
26	572.9 - 574.4 577.5 - 579.0 582.2 - 583.7 587.8 - 589.0		35	847.7 - 848.9 859.0 - 860.5 862.3 - 863.1 872.9 - 874.2 875.9 - 877.2
27	593.0 - 594.4 597.6 - 599.1 602.9 - 604.3 607.8 - 608.9		36	883.0 - 884.4 890.0 - 891.4 902.7 - 904.1 908.8 - 910.1
28	612.8 - 613.6 616.5 - 617.8 623.6 - 625.0 630.0 - 640.0		37	910.9 - 912.2 919.2 - 920.5 924.7 - 926.1 930.6 - 932.0
29	636.7 - 637.7 643.1 - 644.6	· · · · · · · · · · · · · · · · · · ·		936.0 - 937.3 942.0 - 943.3
30	649.8 - 651.3 657.1 - 658.6 664.0 - 665.5		38	956.5 - 957.5 960.0 - 961.3 965.7 - 967.0 971.3 - 972.7
30	671.2 - 672.5 677.6 - 679.0 684.0 - 685.3 690.8 - 692.3 700.0 - 701.7		39	971.3 - 972.7 978.5 - 979.8 988.3 - 989.7 993.5 - 995.0 1000.0 - 1001.5 1007.0 - 1008.5

L3 HEAT FLOW CONDUCTIVITY SAMPLES

Samples 252 - 840 are in feet

252	500
300	600
351	650
400	700
450	750
500	800

Following samples are in metres

660
675
690
705
720
735
750
765
780
795
810
825
840
855
870
885
900
915
930
945
960
975
990

L4-81D PHOTO LOG

Picture #	Box's	Intervals (m)
1	1-4	5.5 - 21.6
2	5–8	21.6 - 37.2
3	9 - 12	37.2 - 53.4
4	13-16	53.4 - 69.8
5	17-20	69.8 - 85.9
6	21-24	85.9 - 104.5
7	25–28	104.5 - 121.0
8	29–32	121.0 - 136.7
9	33–36	136.7 - 153.0
10	37–40	153.0 - 173.7
11	41-44	173.7 - 189.7
12	45-48	189.7 - 206.1
13	49-52	206.1 - 221.6
14	53–56	221.6 - 238.5
15	57–60	238.5 - 252.8
16	61-64	252.8 - 269.4
17	*65,66,67,67A	269.4 - 285.8
18	68-71	285.8 - 302.2
19	72-75	302.2 - 320.6
20	76-79	320.6 - 338.0
21	80-83	338.0 - 354.7
22	84–87	354.7 - 371.1
23	88-91	371.1 - 388.5
24	92-95	388.5 - 405.5
25	96-99	405.5 - 422.4
26	100-101	422.4 - 427.0

^{*} Note box numbering.

L4-82D EXTENSION PHOTO LOG

27	1-4	428.0 - 445.0
28	5–8	445.0 - 462.1
29	9-12	462.1 - 478.5
30	13-16	478.5 - 495.9
31	17-20	495.9 - 513.0
32	21-24	513.0 - 529.7
33	25-28	529.7 - 547.0
34	29-32	547.0 - 563.7
35	33-36	563.7 - 583.0
36	37-40	583.0 - 598.0
37	41-44	598.0 - 615.3
38	45-48	615.3 - 632.3
39	49-52	632.3 - 649.3
40	53 – 56	649.3 - 666.3

Picture #	Box #'s	<pre>Intervals (m)</pre>
41	57-60	666.3 - 689.6
42	61-64	689.6 - 712.7
43	65 - 68	712.7 - 736.1
44	69-72	736.1 - 758.8
45	73-76	758.8 - 781.0
46	77-80	781.0 - 803.0
47	81-84	803.0 - 825.1
48	85-88	825.1 - 847.4
49	89-92	847.4 - 869.7
50	93-96	869.7 - 891.4
51	97-100	891.4 - 914.3
52	101-104	914.3 - 936.9
53	105-108	936.9 - 962.7
54	109-112	962.7 - 984.8
55	113-116	984.8 - 1007.4
56	117-120	1007.4 - 1030.3
57	121-124	1030.3 - 1053.0
58	125-128	1053.0 - 1075.8
59	129-132	1075.8 - 1099.2
60	133-136	1099.2 - 1122.8
61	137-140	1122.8 - 1145.3
62	141-144	1145.3 - 1168.1
63	145-148	1168.1 - 1191.1
64	149-152	1191.1 - 1214.1
65	153-156	1214.1 - 1236.9
66	157-160	1236.9 - 1258.9
67	161-164	1258.9 - 1279.0 (T.D.)

L4 CONDENSED

Box #	Intervals (m)	Box #	Intervals (m)
1	5.5 - 7.0 9.7 - 11.2 13.3 - 14.8	14	168.5 - 169.9 173.7 - 175.2 177.6 - 179.1
2	17.2 - 18.7 22.3 - 23.8 24.7 - 26.2	15	181.7 - 183.2 186.1 - 187.0 189.7 - 191.0
3	31.2 - 32.2 32.6 - 33.9 37.2 - 38.7	16	193.4 - 195.1 197.6 - 198.1 201.8 - 203.1
4	41.4 - 42.9 45.4 - 46.9 49.2 - 50.7	17	206.1 - 207.2 209.7 - 211.0 213.8 - 215.1
5	53.4 - 54.8 57.8 - 59.3 61.9 - 63.0	18	217.5 - 218.7 225.6 - 226.8 233.6 - 235.0
6	65.8 - 67.3 71.5 - 73.0 74.2 - 75.1	19	240.5 - 241.8 245.1 - 248.7 248.9 - 250.1
7	77.8 - 78.9 81.8 - 83.3 85.9 - 87.4	20	252.8 - 254.1 259.8 - 261.1 257.2 - 258.5
8	92.7 - 95.0 97.9 - 99.4 100.6 - 102.0	21	261.1 - 262.4 264.0 \(\displies\) 265.4 265.4 - 266.8
9	104.5 - 105.7 109.1 - 109.9 112.4 - 113.9	22	279.4 - 270.8 273.4 - 275.2 278.0 - 278.8
10	116.8 - 118.3 121.0 - 122.3 124.5 - 126.0	23	281.1 - 282.5 285.8 - 287.1 290.2 - 291.5
11	124.5 - 126.0 128.3 - 129.7 132.5 - 134.0	24	294.4 - 295.8 298.6 - 299.9 302.2 - 304.5
12	136.9 - 138.3 144.9 - 146.1 149.0 - 150.5	25	307.8 - 309.1 312.2 - 313.6 318.0 - 319.3
13	153.0 - 154.2 156.4 - 158.5 163.6 - 165.0	26	321.8 - 323.2 327.8 - 329.1 329.1 - 330.3

L4-81D CONDENSED

Box #	Intervals (m)	Box #	<pre>Intervals (m)</pre>
27	333.7 - 335.0 338.0 - 339.4 342.1 - 343.5	40	495.9 - 497.4 500.0 - 501.5 504.2 - 505.7
28	346.4 - 347.9 350.6 - 352.1 354.7 - 356.3	41	508.8 - 510.2 513.0 - 514.5 517.3 - 518.8
29	359.1 - 360.4 363.5 - 364.8 367.6 - 368.8	42	521.5 - 523.0 525.7 - 527.2 529.7 - 531.1
30	372.1 - 373.6 376.9 - 377.2 380.0 - 381.4	43	534.2 - 535.6 538.5 - 540.0 542.8 - 544.3
31	384.3 - 385.7 387.6 - 389.9 392.8 - 394.1	44	547.0 - 548.5 551.4 - 552.8 555.3 - 536.8
32	398.3 - 399.6 401.2 - 402.5 405.5 - 406.8	45	559.6 - 561.1 563.7 - 565.0 629.0 - 630.5
33	409.6 - 411.0 413.9 - 415.4 418.3 - 419.8	46	572.2 - 573.7 576.6 - 578.1 581.0 - 582.4
34 35	422.4 - 423.8 426.5 - 427.0 432.2 - 433.7	47	585.3 - 586.7 589.6 - 591.0 593.6 - 595.1
•	436.4 - 437.9 440.6 - 442.1	48	598.0 - 599.5 602.6 - 604.1 607.1 - 608.6
36	445.0 - 446.5 449.2 - 450.7 453.5 - 455.0	49	611.0 - 612.5 615.3 - 616.8 619.7 - 621.2
37	457.8 - 459.3 462.1 - 463.6 466.3 - 467.8	50	623.9 - 625.4 628.3 - 629.8 632.3 - 633.8
38	470.3 - 471.8 474.3 - 475.8 478.5 - 480.0	51	636.5 - 638.0 640.8 - 641.3 644.9 - 646.4
39	482.9 - 484.3 487.4 - 488.9 491.7 - 493.2	52	644.9 - 646.4 649.3 - 650.8 653.4 - 654.9 655.0 - 656.5

Box #	Intervals	Box #	Intervals
53	661.2 - 662.7 667.8 - 669.3 672.1 - 673.6 678.0 - 679.5	63	885.4 - 886.9 891.4 - 891.8 896.8 - 898.2 902.3 - 903.7
54	683.7 - 685.2 689.6 - 691.1 695.3 - 696.8 701.5 - 703.0	64	908.3 - 909.8 914.3 - 915.8 920.0 - 921.5 925.5 - 927.0
55	707.1 - 708.6 712.7 - 714.2 718.4 - 719.9 724.4 - 725.9	65	931.1 - 932.6 936.9 - 938.4 943.0 - 944.5 948.3 - 949.8
56	730.1 - 731.6 736.1 - 737.6 741.8 - 743.2 747.9 - 749.3	66	954.0 - 955.5 962.7 - 964.2 968.3 - 969.8 973.4 - 974.9
57	753.4 - 754.8 758.8 - 760.3 764.5 - 766.0 770.2 - 771.7	67	979.2 - 980.7 984.8 - 986.3 990.4 - 991.9 996.4 - 997.9
58	775.3 - 776.8 781.0 - 782.5 787.0 - 788.5 791.7 - 793.2	68	1001.7 - 1003.2 1007.4 - 1008.9 1012.7 - 1014.2 1018.7 - 1020.2
59	797.7 - 799.2 803.0 - 804.5 808.9 - 810.4 814.0 - 815.5	69	1024.5 - 1026.0 1030.3 - 1031.8 1035.9 - 1037.4 1041.5 - 1043.0
60	819.6 - 821.1 825.4 - 826.5 831.2 - 832.7 836.3 - 837.8	70	1047.4 - 1048.9 1053.0 - 1054.5 1058.4 - 1059.9 1069.0 - 1070.5
61	841.8 - 843.2 847.2 - 848.7 853.3 - 854.7 859.0 - 860.5	71	1070.6 - 1072.1 1075.8 - 1077.3 1089.0 - 1090.5 1091.7 - 1093.2
62	864.0 - 865.5 869.7 - 871.2 874.8 - 876.3 879.7 - 881.1	72	1093.5 - 1095.0 1103.8 - 1105.3 1105.3 - 1106.8 1111.7 - 1113.2

Box #	Intervals
73	1117.4 - 1118.9 1124.3 - 1125.8 1128.5 - 1130.0 1134.5 - 1136.0
74	1139.9 - 1141.4 1146.9 - 1148.4 1151.1 - 1152.6 1157.2 - 1158.7
75	1162.5 - 1164.0 1168.1 - 1169.6 1173.7 - 1175.2 1179.5 - 1181.0
76	1185.4 - 1186.9 1191.1 - 1192.6 1196.5 - 1198.0 1202.6 - 1204.0
77	1208.4 - 1209.9 1214.1 - 1215.6 1220.0 - 1221.5 1225.7 - 1227.2
78	1230.9 - 1232.3 1256.9 - 1258.4 1242.2 - 1243.7 1247.5 - 1249.1
79	1253.3 - 1254.8 1258.9 - 1260.4 1264.5 - 1266.0 1270.0 - 1271.5
80	1276.0 - 1277.5

L4-81D HEAT FLOW CONDUCTIVITY SAMPLES (m)

15	645
30	660
45	675
60	690
75	705
90	720.
105	735
120	750
135	765 700
150 165	780 795
180	810
195	825
210	840
225	855
240	870
255	885
270	900
285	915
300	930
315	945
330	960
345	975
360	990
375 390	1005 1020
405	1020
420	1050
435	1065
450	1080
465	1095
480	1110
495	1125
510	1140
525	1155
540	1170
555	1185
570	1200
585	1215
600 615	1230 1245
630	1245
030	1275
	1213

L5-81D PHOTO LOG

Picture #	Box #'s	<pre>Intervals (m)</pre>
1	1-4	221.6 - 241.1
2	5-8	241.1 - 264.0
3	9-12	264.0 - 301.8
4	13-16	301.8 - 333.2
5	17-20	333.2 - 350.3
6	21-24	350.3 - 373.0
7	25-28	373.0 - 396.5
8	29-32	396.5 - 419.2
9	33–36	419.2 - 440.9
10	37-40	440.9 - 462.7
11	41-44	462.7 - 484.8
12	45-48	484.8 - 505.9
13	49-52	505.9 - 527.9
14	53-56	527.9 - 550.0
15	57-60	550.0 - 573.2
16	61-64	573.2 - 595.5
17	65–6 8	595.5 - 617.7
18	69-72	617.7 - 640.0
19	73–76	640.0 - 662.1

L5-81D CONDENSED

Box #	Intervals (m)	Box #	Intervals (m)
1	221.6 - 223.0 225.6 - 228.2 232.1 - 233.9	12	452.2 - 453.7 457.8 - 459.3 462.7 - 463.8 468.1 - 469.3
2	236.6 - 238.1 241.1 - 242.9 245.6 - 247.6	13	473.5 - 475.0 479.3 - 480.7 484.4 - 485.6
3	251.4 - 254.8 259.1 - 260.6 264.0 - 265.6	14	489.6 - 490.9 494.7 - 496.2
4	269.3 - 270.8 286.0 - 288.3		500.1 - 501.6 505.9 - 507.4 512.0 - 513.4
	292.7 - 294.4	15	516.6 - 518.1 521.1 - 523.6
5	301.8 - 303.8 307.7 - 317.0 327.0 - 328.5		527.9 - 529.4 533.2 - 534.7
6	329.8 - 331.3 333.2 - 334.6 337.3 - 338.8	16	538.8 - 540.3 544.3 - 545.8 550.0 - 551.5 555.0 - 556.5
7	339.0 - 340.4 344.6 - 346.0 350.3 - 351.8 355.9 - 357.4	17	561.3 - 562.8 567.0 - 568.5 573.2 - 574.6
8	361.8 - 363.3		578.6 - 580.0
	367.3 - 368.8 373.0 - 374.5 378.9 - 380.3	18	584.2 - 585.7 589.8 - 590.2 595.5 - 597.0 601.3 - 602.8
9	385.0 - 386.5 390.8 - 392.2 396.5 - 397.9 402.0 - 403.5	19	607.1 - 608.6 612.9 - 613.8 617.7 - 619.2 623.4 - 624.9
10	407.6 - 408.9 413.5 - 415.0 419.2 - 420.7 425.0 - 426.5	20	629.0 - 630.5 634.4 - 635.9 640.0 - 641.5 645.7 - 647.1
11	429.9 - 431.4 435.1 - 436.5 440.9 - 442.2 446.4 - 447.9	21	650.7 - 652.2 656.2 - 657.7

L5-81D HEAT FLOW CONDUCTIVITY SAMPLES (m)

L6-81D PHOTO LOG

Picture #	Box's	<pre>Intervals (m)</pre>
1 2	1-4 5-8	5 - 20.8 20.8 - 36.5
3	9-12	36.5 - 52.9
4	13-16	52.9 - 68.3
5	17-20	68.3 - 84.8
6	21-24	84.8 - 100.0
7	25-28	100.0 - 116.2
8	29–32	116.2 - 133.0
9	33–36	133.0 - 149.5
10	37-40	149.5 - 165.9
11	41-44	165.9 - 182.9
12	45-48	182.9 - 200.0
13	49-52	200.0 - 217.0
14	53-56	217.0 - 234.5
15	57-60	234.5 - 251.2
16	61-64	251.2 - 267.9 (Reduced to NQ)
17	65–68	267.9 - 291.2
18	69-72	291.2 - 313.8
19	73 -7 6	313.8 - 336.0
20	77–80	336.0 - 358.0
21	81-84	358.0 - 381.4
22	85–88	381.4 - 404.4
23	89-92	404.4 - 427.4
24	93–96	427.4 - 449.5
25	97-100	449.5 - 473.5
26	101-104	473.5 - 497.3
27	105-108	497.3 - 521.8
28	109-112	521.8 - 544.8
29	113-116	544.8 - 567.5
30	117-118	567.5 - 579.2 (T.D.)

L6-81D CONDENSED

Box #	Intervals (m)	Box #	<pre>Intervals (m)</pre>
1	5.0 - 6.5 9.9 - 11.4 14.0 - 15.5	12	137.2 - 138.7 141.2 - 142.6 145.2 - 146.7
2	17.3 - 18.6 20.6 - 22.1 26.1 - 27.6	13	150.8 - 152.1 153.5 - 155.0 157.3 - 158.8
3	28.4 - 29.9 32.5 - 34.0 36.8 - 37.3	14	161.7 - 163.1 167.4 - 168.9 170.4 - 171.8
4	40.6 - 41.8 44.5 - 46.0 48.9 - 50.4	15	174.6 - 176.1 178.5 - 180.0 182.9 - 184.3
5	52.6 - 54.1 56.6 - 58.0 62.0 - 63.4	16	181.5 - 183.0 191.4 - 192.8 195.7 - 197.1
6	64.6 - 66.0 68.3 - 69.8 72.2 - 73.7	17	200.0 - 201.4 204.3 - 205.7 208.6 - 210.0
7 .	77.7 - 79.1 83.5 - 84.8 84.8 - 86.2	18	212.9 - 214.4 217.0 - 218.5 221.4 - 222.9
8	88.7 - 89.9 93.8 - 95.2 96.0 - 97.4	19	225.9 - 227.4 230.2 - 231.7 235.5 - 237.0
9	100.0 - 101.5 104.2 - 105.6 107.7 - 109.2	20	238.8 - 240.3 242.4 - 243.9 246.9 - 248.4
10	113.5 - 115.0 116.3 - 117.7 120.6 - 122.0	21	255.0 - 256.5 256.1 - 257.6
11	124.5 - 126.0 128.7 - 130.2 136.0 - 137.2	22	259.8 - 261.3 264.8 - 266.3 267.9 - 269.3

Box #	Intervals (m)	Box #	Intervals (m)
23	275.3 - 276.8 279.7 - 281.0 288.1 - 289.6 292.5 - 293.9	31	455.9 - 457.4 462.0 - 463.4 467.9 - 469.3 476.3 - 477.8
24	296.8 - 298.3 302.5 - 304.0 311.0 - 312.5 315.2 - 316.7	32	480.0 - 481.3 484.2 - 485.7 490.1 - 491.6 496.9 - 500.7
25	321.9 - 323.2 325.5 - 327.0 330.3 - 331.8	33	506.2 - 508.9 512.5 - 513.9 517.7 - 518.9
26	336.0 - 337.4 343.2 - 344.7 347.5 - 349.0 356.3 - 357.8	34	524.0 - 525.5 529.4 - 530.8 533.8 - 535.2 539.4 - 540.9
27	360.5 - 361.9 364.5 - 365.9 370.0 - 371.4	35	546.6 - 548.1 553.5 - 555.0 556.2 - 557.7 564.9 - 566.3
28	378.9 - 380.3 384.2 - 385.6 387.3 - 388.7	36	571.8 - 573.2 574.5 - 576.0
	394.4 - 395.8 401.6 - 403.1 405.3 - 406.7		
29	410.7 - 412.2 415.8 - 417.2 421.5 - 423.0 431.6 - 433.2		
30	433.2 - 434.7 439.1 - 440.6 444.9 - 446.4 450.3 - 451.8		

L6-81D HEAT FLOW CONDUCTIVITY SAMPLES (m)

L7 PHOTO LOG

Picture #	Box #'s	<pre>Intervals (m)</pre>
1	1-4	5.5 - 28.8
2	5–8	28.8 - 50.6
3	9-12	50.6 - 76.5
4	13-16	76.5 - 98.0
5	17-20	98.0 - 120.0
6	21-24	120.0 - 143.3
7	25-28	143.3 - 163.7
8	29-32	163.7 - 185.5
9	33–36	185.5 - 209.5
10	37-40	209.5 - 231.2
11	41-44	231.2 - 254.5
12	45-48	254.5 - 276.9
13	49-52	276.9 - 300.0
14	53-56	300.0 - 322.4
15	57 – 60	322.4 - 346.5
16	61-64	346.5 - 366.5
17	65–68	366.5 - 389.3
18	69–72	389.3 - 414.6
19	73	414.6 - 417.9

L7 CONDENSED

Box #	<pre>Intervals (m)</pre>	Box 4	Intervals (m)
1	11.0 - 12.5 16.6 - 18.1 20.4 - 21.9 23.5 - 25.0	10	211.0 - 212.5 215.4 - 216.9 220.4 - 221.9 230.0 - 231.5
2	29.8 - 31.2 34.1 - 35.6 40.5 - 42.0 45.0 - 46.5	11	235.3 - 236.8 236.8 - 238.3 245.4 - 246.9 252.4 - 253.9
3	50.7 - 52.2 58.8 - 60.3 62.9 - 64.4 75.1 - 76.6	12	257.7 - 259.2 262.8 - 264.3 267.3 - 268.8 272.5 - 274.0
4	78.0 - 79.5 86.1 - 87.6 88.8 - 90.3 95.2 - 96.7	13	281.1 - 282.6 285.1 - 288.6 288.6 - 290.1
5	99.5 - 101.0 107.5 - 109.0 111.7 - 113.2 114.5 - 116.0	14	294.5 - 296.0 303.7 - 305.2 309.0 - 310.5 314.8 - 316.3
6	120.7 - 122.2 126.0 - 127.5 134.8 - 136.3 139.0 - 140.5	15	317.9 - 319.4 323.8 - 325.3 328.0 - 329.5 334.3 - 334.8
7	143.9 - 145.4 148.4 - 149.9 154.3 - 155.8 162.2 - 163.7	16	341.0 - 342.5 355.7 - 357.2 357.2 - 358.7 362.5 - 364.0
8	166.7 - 168.2 169.6 - 171.1 177.5 - 179.0 181.7 - 183.2	17	367.9 - 369.4 372.8 - 374.3 378.7 - 380.2 386.1 - 387.6
9	191.0 - 192.5 195.7 - 197.2 200.0 - 201.5 208.3 - 209.8	18	346.5 - 348.0 397.0 - 398.5 401.1 - 402.6 407.0 - 408.5
		19	416.4 - 417.9

L7 HEAT FLOW CONDUCTIVITY SAMPLES (m)

L8 PHOTO LOG

Picture #	Box #'s	<pre>Intervals (m)</pre>
1	1-4	3.7 - 24.9
2	5–8	24.9 - 48.1
3	9-12	48.1 - 69.6
4	13-16	69.6 - 92.9
5	17-20	92.9 - 115.4
6	21-24	115.4 - 137.2
7	25-28	137.2 - 160.2
8	29-32	160.2 - 183.8
9	33–36	183.8 - 205.8
10	37-40	205.8 - 227.5
11	41-44	227.5 - 250.0
12	45-48	250.0 - 273.0
13	49-52	273.0 - 295.2
14	53-56	295.2 - 319.1
15	57-60	319.1 - 342.5
16	61-64	342.5 - 364.9
. 17	65-68	364.9 - 387.8
18	69-72	387.8 - 410.4
19	73-76	410.4 - 432.6
20	77-80	432.6 - 453.8
21	81-84	453.8 - 475.5 (T.D.)

L8 CONDENSED

Box #	Intervals (m)	Box #	Intervals (m)
1	3.7 - 5.2 8.8 - 10.3 16.0 - 17.5 20.0 - 21.5	11	227.5 - 229.0 233.4 - 234.9 238.0 - 239.5 244.5 - 246.0
2	24.9 - 26.4 34.5 - 36.0 36.2 - 37.7 43.1 - 44.6	12	250.0 - 251.5 255.6 - 257.1 261.3 - 262.8 267.1 - 268.6
3	48.1 - 49.6 52.7 - 54.2 58.5 - 60.0 64.2 - 65.7	13	273.0 - 274.5 281.3 - 282.8 284.3 - 285.8 290.0 - 291.5
4	71.0 - 72.5 77.0 - 78.5 84.1 - 85.6 87.0 - 88.5	14	295.2 - 296.7 301.3 - 302.8 307.3 - 308.8 313.2 - 314.7
5	92.9 - 94.4 99.5 - 101.0 107.5 - 109.0 109.8 - 111.3	15	319.1 - 320.6 324.9 - 326.4 332.4 - 333.9 336.7 - 338.2
6	115.4 - 116.9 121.0 - 122.5 126.5 - 128.0 131.8 - 133.3	16	342.5 - 344.0 348.0 - 349.5 353.8 - 355.3 359.3 - 360.8
7	137.2 - 138.7 142.7 - 144.2 148.1 - 149.6 154.1 - 155.6	17	364.9 - 366.4 370.9 - 372.4 376.9 - 378.4 382.8 - 384.3
8	160.2 - 161.7 166.9 - 168.4 175.0 - 176.5 178.4 - 179.9	18	387.8 - 389.3 395.9 - 397.4 398.9 - 400.4 406.1 - 407.6
9	183.8 - 185.3 189.5 - 191.0 194.6 - 195.9 200.1 - 201.6	19	410.4 - 411.9 416.0 - 417.5 421.3 - 422.8 427.0 - 428.5
10	205.8 - 207.3 210.8 - 212.3 216.1 - 217.6 221.8 - 223.3	20	432.6 - 434.1 438.4 - 439.9 443.7 - 445.2 448.4 - 449.9
		21	453.7 - 455.2 459.1 - 460.6 467.7 - 469.2

473.0 - 474.5

L8 HEAT FLOW CONDUCTIVITY SAMPLES (m)