PROJECT No.: 11-1436-0082 / 5000

CLIENT: 8360 Wiggins Holdings Inc.
PROJECT: Oxford Riverbend
LOCATION: 8255 and 8360 Wiggins St. and 5279 Riverbend Dr., Burnaby, B.C.

RECORD OF MONITORING WELL: MW15-01

DRILLING DATE: November 30, 2015

SHEET 1 OF 1
DATUM: Ground Surface

DRILLING RIG: Track Mounted Auger Drill
DRILLING METHOD: Solid and Hollow Steam Auger (152 mm)

DEPTH SCALE METRES	DESCRIPTION	ELEV. / DEPTH (m)	NUMBER	TYPE	BLOWS/0.3m	CORE No.	CORE RECOVERY %
	Ground Surface						
0	**(SP/GP)** silty SAND and GRAVEL, fine to medium; no staining, no odour; non-cohesive, moist, loose.	0.00					
1							
2							
3	- dark grey at 3.05m depth.						
4	**(ML)** sandy SILT, fine to medium sand, some gravel; dark grey, no staining, no odour; non-cohesive, moist, firm.	4.27	1	AS			
5	**(SW)** SAND, fine to medium, trace silt; grey, no staining, no odour; non-cohesive, wet, loose.	4.88	2	AS			
6	**(PT)** PEAT, some silt, some wood debris; black, no staining, no odour.	5.79	3	AS			
7	**(OL)** ORGANIC SILT; grey to dark grey, no staining, no odour; moist. - some peat at 7.32m depth. - grey at 7.47m depth.	6.71	4	AS			
8							
9							
	End of Monitoring Well.	9.14					
10							

PID ppm: 5, 10, 15, 20
PID ppm: 50, 100, 150, 200

DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m: 20, 40, 60, 80

WATER CONTENT PERCENT: Wp — W — Wl; NP, Non-Plastic; 10, 20, 30, 40

ADDITIONAL LAB. TESTING

PIEZOMETER, STANDPIPE OR THERMISTOR INSTALLATION

PVC Stick-up
Filter Sand
Bentonite Chips
Filter Sand
Slotted PVC Pipe
Bentonite Chips

DEPTH SCALE
1 : 50

SOIL CLASSIFICATION SYSTEM: GACS
LOGGED: VP
CHECKED: AV

REV: A.2

Golder Associates

National IM Server:GINT_GAL_NATIONALIM Unique Project ID: Output Form:BC_BOREHOLE (ENVIRO) kvike 12/29/15

Disclaimer: For Environmental Purposes Only