

SEACOR JOB NO: C0006-108

DEPTH (m)	SAMPLE TYPE	SOIL TYPE	SOIL DESCRIPTION	TEST DATA				WELL COMPLETION	WATER LEVEL	FIELD NOTES	DEPTH (m)
				HYDROCARBON VAPOUR LEVEL (ppmv)							
				10	100	1000	10000				
0.0 - 1.4		FILL	fine to medium grained sand, trace gravel, trace organics, some silt, brown, moist							bentonite seal	
1.4 - 2.4			grey at 1.4 m	10						June 16/97	
2.4 - 3.1		SAND (NATIVE)	silty, fine to medium grained, trace cobbles difficult drilling at 2.4 m							BETX/VPH	
3.1 - 4.42			wet at 3.1 m			750	500			50 mm 010 slotted PVC	
4.42 - 5.33			some silt, grey, moist at 4.42 m		220					silica sand	
5.33			End of borehole at 5.33 m Screened interval from 0.76 m to 5.33 m Elevation at Top of Piezometer (T.O.P.) = 99.169 m Depth to groundwater from T.O.P. = 2.470 m	45							

DRILLING METHOD: Rotary Auger; logged by GF

DATE DRILLED: 6/13/97

Notes:

-  NO RECOVERY
-  AUGER SAMPLE
-  SPLIT SPOON SAMPLE
-  CONTINUOUS SAMPLE