

PROJECT COURTAULDS COATINGS LOCATION 126 HARBOUR AVENUE NORTH VANCOUVER, BC
 SURFACE ELEVATION _____ CASING TOP ELEVATION 99.80
 START 7/24/95 FINISH 7/24/95
 SAMPLER MITLAMs MONITORING DEVICE PID HNU PI-101
 SUBCONTRACTOR AND EQUIPMENT SONIC DRILLING LTD. SONIC VIBRATORY DRILLING
 COMMENTS SAMPLES COLLECTED FROM A CONTINUOUS CORE

PENETRATION RESULTS	Sample Depth Interval, feet	PID Reading (ppm)	Depth Below Surface, feet	Depth Below Surface, meters	Lithologic Description	Unified Soil Classification	Well Construction Details
			0	0	Gross, Fibrous, organics		
					Sand, light brown, fine grained, some silt, dry	SM	
			1		Sand, brown, medium to coarse grained, some rounded gravel, dry	SP	
					Gravel, well graded, rounded, trace cobbles, some medium to coarse grained sand, brown, dry	GW	
		LTDL	5				
					Moist @ 2.4m		
		1	2				
					Gray, wet @ 2.7m, slight hydrocarbon-like odor, oily appearance		
		250	3				
					Gray, cobbly, trace coarse grained sand, saturated @ 4.3m, hydrocarbon-like odor		
		200	4				
		120	5				
					Sand, brown with red fissures, fine grained, trace silt, trace fine rounded gravel, saturated	SP	
		6	6		Gravel, red to reddish brown, some cobbles, some coarse grained sand, saturated	GW	
		7	7				
					Sand, grayish brown, some silt, trace gravel, saturated	SM	
					Gravel, rounded gravel, trace cobbles, some coarse grained sand, saturated	GW	
					Boring terminated at 9.8m.		
					Groundwater encountered at approximately 4.3m during drilling.		
					Boring converted to a groundwater monitoring well on 7/24/95.		
					LTDL=Less than detection limit		
			35				