

SEACOR ENVIRONMENTAL ENGINEERING I

CLIENT: CANADIAN TURBO (1993) INC.
 PROJECT: Payless Service Station #28
 5246 Cordova Bay Road
 Victoria, B.C.

BOREHOLE LOG

BOREHOLE NO: BH 2
 GROUND ELEVATION: 100.17 m

SEACOR JOB NO: N0031-200

DEPTH (m)	SAMPLE TYPE	SOIL DESCRIPTION	TEST DATA				WELL COMPLETION	WATER LEVEL	FIELD NOTES	DEPTH (m)
			COMBUSTIBLE VAPOUR LEVEL (ppmv)							
			10	100	1000	10000				
0.0 - 1.0	GRAVEL SAND(Fill)	Fine grained, trace silt, trace to some fine grained subangular to subrounded gravel, compact, light brown, damp. No hydrocarbon odour or hydrocarbon staining							road box bentonite seal solid PVC pipe	1.0
1.0 - 2.0	SAND(Native)	Fine to medium grained, trace silt, trace fine grained subangular to subrounded gravel, compact, medium brown and damp. No hydrocarbon odour or hydrocarbon staining. Trace to some gravel.								2.0
2.0 - 3.0		Light hydrocarbon odour and moderate hydrocarbon staining.								3.0
3.0 - 4.0									020 slotted PVC pipe	4.0
4.0 - 5.0		Trace to some silt.							March 19, 1997	5.0
5.0 - 6.0		Saturated, grey, heavy hydrocarbon odour and moderate hydrocarbon staining.								6.0
6.0 - 7.0		Medium to coarse grained sand, moderate hydrocarbon odour.								7.0
7.0 - 8.0		Moderate hydrocarbon staining.								8.0
8.0 - 9.0									soil cuttings	9.0
		End of borehole at 9.60 m Screened Interval from 1.52 m to 9.60 m bgs Elevation at Top of Piezometer (TOP) = 100.06 m Depth to Groundwater from TOP = 4.16 m Monitoring Well Vapour Level = 6600 ppmv								

DRILLING METHOD: hollow stem/split spoon auger

DATE DRILLED: 3/13/97

Notes:





-  NO RECOVERY
-  AUGER SAMPLE
-  SPLIT SPOON SAMPLE
-  CONTINUOUS SAMPLE

PLATE NO. 1

Sheet 1 of 1