

SEACOR
ENVIRONMENTAL ENGINEERING INC.

CLIENT: **CANADIAN TURBO (1993) INC.**
PROJECT: Payless Service Station #68
894 Goldstream Avenue
Langford, B.C.

BOREHOLE LOG

BOREHOLE NO: **BH 2**
GROUND ELEVATION: 100.21 m

SEACOR JOB NO: N0031-202

| DEPTH (m) | SAMPLE TYPE | SOIL TYPE | SOIL DESCRIPTION | TEST DATA | | | | WELL COMPLETION | WATER LEVEL | FIELD NOTES | DEPTH (m) |
|-----------|-------------|-----------|---|---------------------------------|-----|------|-------|-----------------|-------------|----------------------|-----------|
| | | | | COMBUSTIBLE VAPOUR LEVEL (ppmv) | | | | | | | |
| | | | | 10 | 100 | 1000 | 10000 | | | | |
| 0.0 | | | ASPHALT (75 mm) | | | | | | | | |
| 0.0 | | | GRAVEL Coarse sand, fine to coarse rounded to subrounded gravel, loose, brown and damp. No hydrocarbon odours and no hydrocarbon staining. Cobbles. | | | | | | | road box | |
| 1.0 | | | No hydrocarbon odours and no hydrocarbon staining. | | | | | | | bentonite seal | |
| 2.0 | | | No hydrocarbon odours and no hydrocarbon staining. | | | | | | | | |
| 3.0 | | | No hydrocarbon odours and no hydrocarbon staining. | | | | | | | | |
| 4.0 | | | Moist. | | | | | | | silica sand | |
| 5.0 | | | Cobbles. | | | | | | | | |
| 6.0 | | | Wet. | | | | | | | 010 slotted PVC pipe | |
| 7.0 | | | SAND Coarse, some fine to coarse rounded to subrounded gravel, compact, brown and moist. No hydrocarbon odours and no hydrocarbon staining. Wet. | | | | | | | Apr. 25/97 | |
| 8.0 | | | No hydrocarbon odours and no hydrocarbon staining. | | | | | | | | |
| 9.0 | | | End of Borehole at 9.15 m Screened Interval from 4.57 m to 9.15 m bgs Elevation at Top of Piezometer (TOP) = 100.14 m Depth to Groundwater from TOP = 6.39 m Monitoring Well Vapour Level = 50 ppmv | | | | | | | | |

DRILLING METHOD: B-53 Auger Rig

DATE DRILLED: 4/17/97

Notes:





-  NO RECOVERY
-  AUGER SAMPLE
-  SPLIT SPOON SAMPLE
-  CONTINUOUS SAMPLE

PLATE NO. 1

Sheet 1 of 1