

# MONITORING WELL ID: Typical Monitoring Well Log



**Well Type:** Groundwater Monitoring Well

**Project Location:** 33765 Pine Street, Abbotsford, BC

**Drilling Contractor:** Uniwide Drilling Co. Ltd.

**Drilling Equipment/Method:** Track Mounted - Solid Stem Auger

**Well Location:** East portion of the Site

**Project Name/No.:** 11749

**Client:**

**Engineer/Geologist:**

**Drill Date:** February 22, 2016

**Page:** 1 of 2

Depth (ft/m)	Symbol	Soil / Sediment Description	Sample Type	% Recovery	Sample Analyzed	Sample ID	Headspace (PID)	Well Construction	Remarks
							0 500 1000 1500 2000 ppm		
ft m									
-4									
-3									
-2									
-1									
0	0	Ground Surface <b>COBBLES</b>							
1	1	Cobbles <b>Sandy SILT</b> Brown, fine grained Sandy SILT, stiff, moist, low plasticity, odours and staining not observed.							
2	2								
3	1								
4	4								
5	5								
6	2	<b>SAND and GRAVEL</b> Brown, fine to medium grained SAND & medium to coarse grained GRAVEL with trace silt and cobbles, dense, moist, odours and staining not observed.							
7	7	Moist to wet at approximately 3.5 mbg.							
8	8								
9	9								
10	3								
11	11								
12	12								
13	4								
14	14								
15	15								

*Any use which a third party makes of this document, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CSAP/MOE/Keystone Environmental Ltd. are not responsible for any use or modification of this document. CSAP/MOE/Keystone Environmental Ltd. accept no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions taken based on this document.*

Date of Water Level: February 24, 2016	Well-Borehole Diameter: 0.15 m	Depth of Well (TOC): 8.3 m
Water Level (from TOC): 7.5 m	Well Casing Diameter: 0.05 m	
	Well Casing Material: Schedule 40 PVC	
	Well Screen Slot Size: 0.0025 m	

# MONITORING WELL ID: Typical Monitoring Well Log



**Well Type:** Groundwater Monitoring Well

**Project Location:** 33765 Pine Street, Abbotsford, BC

**Drilling Contractor:** Uniwide Drilling Co. Ltd.

**Drilling Equipment/Method:** Track Mounted - Solid Stem Auger

**Well Location:** East portion of the Site

**Project Name/No.:** 11749

**Client:**

**Engineer/Geologist:**

**Drill Date:** February 22, 2016 **Page:** 2 of 2

Depth (ft/m)	Symbol	Soil / Sediment Description	Sample Type	% Recovery	Sample Analyzed	Sample ID	Headspace (PID)					Well Construction	Remarks
							0	500	1000	1500	2000		
16 5	[Symbol: Dotted pattern]	<p><b>SAND</b> Brown, fine to medium grained SAND with trace fine to medium grained gravel, dense, moist, odours and staining not observed.  Saturated at approximately 6.0 mbg.</p>											
17													
18													
19													
20 6													
21													
22													
23 7		End of Hole											
24	<div style="border: 1px solid red; padding: 5px; color: red;"> <p><i>Any use which a third party makes of this document, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CSAP/MOE/Keystone Environmental Ltd. are not responsible for any use or modification of this document. CSAP/MOE/Keystone Environmental Ltd. accept no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions taken based on this document.</i></p> </div>											Well Screen and 10/20 Silica Sand	
25													
26 8													
27													
28													
29													
30 9													
31													
32													
33 10													
34													
35													

Date of Water Level: February 24, 2016  
Water Level (from TOC): 7.5 m

Well-Borehole Diameter: 0.15 m  
Well Casing Diameter: 0.05 m  
Well Casing Material: Schedule 40 PVC  
Well Screen Slot Size: 0.0025 m

Depth of Well (TOC): 8.3 m