

SEACOR ENVIRONMENTAL INC.

CLIENT: **HUSKY OIL**
 PROJECT: **SS# 5287**
591 Highway 97
100 Mile House, BC

BOREHOLE LOG


BOREHOLE NO: **BH 20**
 ELEVATION: **97.66**

SEACOR JOB NO: 204.02358.500

DEPTH (m)	SAMPLE TYPE	SOIL TYPE	SOIL DESCRIPTION	TEST DATA				WELL COMPLETION	WATER LEVEL	FIELD NOTES	DEPTH (m)
				HYDROCARBON VAPOUR LEVEL (ppmv)							
				1	10	100	1000				
0.0		ASPHALT								Concrete & roadbox	0.0
0.0		SAND	- fine to coarse grained, some gravel, trace silt, brown, moist								0.0
0.5		SILT	- some sand, brown, moist							Bentonite seal	0.5
1.0											1.0
1.5										Backfilled with sand	1.5
2.0											2.0
2.5		SAND	- fine to coarse grained, brown, moist								2.5
3.0		SILT	- some sand, brown, moist							Bentonite seal	3.0
3.5											3.5
4.0										Backfilled with silica sand	4.0
4.5											4.5
5.0											5.0
5.5			- wet at 5.5 m							GW = 5.50 m (June 21/01)	5.5
6.0											6.0
6.7			End of borehole at 6.7 m; Bedrock encountered 50 mm diam, 010 slot, PVC monitoring well installed Screened interval = 3.7 to 6.7 m								6.7
			Top of Piezometer (TOP) elevation = 97.56 m Depth to groundwater from TOP = 5.39 m (06/21/01) Groundwater elevation = 92.17 m (06/21/01) Borehole combustible vapour level = 350 ppmv (06/21/01)								

DRILLING METHOD: Auger - solid stem Logged by JH

DATE DRILLED: 06/18/01

Notes:  AUGER SAMPLE