

SEACOR ENVIRONMENTAL INC.

CLIENT: Amacon-Onni (Davie) Inc.
 PROJECT: Seymour and Davie
 1133 - 1199 Seymour Street
 Vancouver, BC

BOREHOLE LOG

BOREHOLE NO: BHM1
 ELEVATION: 21.894

SEACOR JOB NO: 201.00951.001

| DEPTH (m) | SAMPLE TYPE | SOIL TYPE | SOIL DESCRIPTION | TEST DATA | | | | WELL COMPLETION | WATER LEVEL | FIELD NOTES | DEPTH (m) |
|--|-------------|--------------|--|---------------------------------|-----|------|-------|-----------------|-------------|---------------------------|-----------|
| | | | | HYDROCARBON VAPOUR LEVEL (ppmv) | | | | | | | |
| | | | | 10 | 100 | 1000 | 10000 | | | | |
| 0.0 - 1.0 | | ASPHALT FILL | Silty, fine to medium sand, some medium to coarse gravel, trace black staining, brown, moist | 45 | | | | | | Roadbox, J-plug, concrete | |
| 1.0 - 2.0 | | | | 75 | | | | | | | |
| 2.0 - 3.0 | | | | 20 | | | | | | | |
| 3.0 - 4.0 | | SILTY SAND | Silty, fine sand, some fine to medium gravel, grey and brown, moist, very difficult drilling | 10 | | | | | | Bentonite | |
| 4.0 - 5.0 | | | | 25 | | | | | | | |
| 5.0 - 6.0 | | SAND | Poorly-graded, fine sand, grey and brown, moist | 25 | | | | | | | |
| 6.0 - 7.0 | | | | 10 | | | | | | 50mm PVC Pipe | |
| 7.0 - 8.0 | | | | 10 | | | | | | | |
| 8.0 - 9.0 | | | | | | | | | | | |
| 9.0 - 10.0 | | | | | | | | | | | |
| 10.0 - 11.0 | | | | | | | | | | | |
| 11.0 - 12.0 | | | | | | | | | | 10/20 Silica Sand | |
| 12.0 - 13.0 | | | | 20 | | | | | | (05/24/02) | |
| 13.0 - 14.0 | | | | 25 | | | | | | 50mm Ø10 Slot PVC Screen | |
| 14.0 - 15.0 | | | | 25 | | | | | | | |
| 15.0 - 16.0 | | | | 40 | | | | | | Bottom Cap | |
| 16.0 - 16.8 | | | | | | | | | | Slough | |
| End of borehole = 16.8 m Screened interval = 12.3 m to 15.3 m Elevation at top of piezometer (T.O.P.) = 21.734 m Depth to groundwater from T.O.P. = 12.269 m (05/24/02) | | | | | | | | | | | |

DRILLING METHOD: Auger - Uniwide - log by dsf

DATE DRILLED: 5/24/02

Notes:

-  NO RECOVERY
-  AUGER SAMPLE
-  SPLIT SPOON SAMPLE
-  CYCLONE RETURN (HAMMER)