


DEPTH (m)	SAMPLE TYPE	SAMPLE ID	SPT COUNT	SOIL TYPE	SOIL DESCRIPTION	FIELD TEST DATA				WELL COMPLETION	WATER LEVEL	WELL COMPLETION NOTES	DEPTH (m)
						ORGANIC VAPOUR LEVEL (ppmv)							
						1	10	100	1000				
0					Ground Surface								0.0
0.0 - 1.0				ASPHALT SAND AND GRAVEL	medium sand and subrounded gravel, trace cobbles, frozen from 0 to 0.6 m, brown, moist			75				stickup, plug cement bentonite seal	1.0
1.0 - 2.0								75					2.0
2.0 - 3.0												backfilled with drill cuttings	3.0
3.0 - 4.0													4.0
4.0 - 5.0													5.0
5.0 - 6.0												bentonite seal	6.0
6.0 - 7.0													7.0
7.0 - 8.0													8.0
8.0 - 9.0													9.0
9.0 - 10.0													10.0
10.0 - 11.0												silica sand 50 mm 010 slot PVC pipe	11.0
11.0 - 12.0								150					12.0
12.0 - 13.0													13.0
13.0 - 14.0													14.0
14.0 - 15.0				SILTY CLAY	brown, moist								15.0
15.0 - 16.0								150					16.0
16.0 - 16.8					- colour change to black at 16.7 m, shale-like End of borehole at 16.8 m							slough	16.8

Well Completion Details:
Screened interval from 6.1 m to 15.2 m below surface
Elevation at top of pipe (TOP) = 98.130 m

Drilled by Beck Drilling and Environmental Services Ltd. of Vancouver, BC

SEACOR CANADA V5 201.01018 - CLOSURE REPORT.GPJ SEACOR CANADA V5.GDT 04/21/06

DRILLING METHOD: Solid Stem Auger Drilling
BOREHOLE DIAMETER: 0.112 m (OD)

Notes:  AUGER SAMPLE

DRILL DATE: December 07, 1992 LOGGED BY: JR