

SEACOR JOB NO: 205.03066.02

| DEPTH (m) | SAMPLE TYPE | SAMPLE ID | SPT COUNT | SOIL TYPE | SOIL DESCRIPTION | FIELD TEST DATA | | | | WELL COMPLETION | WATER LEVEL | WELL COMPLETION NOTES | ELEVATION (m) |
|---|-------------|-----------|---------------|--|--|-----------------------------|----|-----|------|-----------------|--------------------------|-----------------------|---------------|
| | | | | | | ORGANIC VAPOUR LEVEL (ppmv) | | | | | | | |
| | | | | | | 1 | 10 | 100 | 1000 | | | | |
| 0.0 | | | 2 | ASPHALT FILL | ASPHALT FILL | | | | | | Roadbox, plug, cement | 3.00 | |
| 0.0 - 1.0 | A/B | | 2, 3, 4 | Clayey silt, trace sand, dark grey, trace brick debris | Clayey silt, trace sand, dark grey, trace brick debris | | | | | | Bentonite seal | 2.934 | |
| 1.0 - 2.0 | C | | 3, 3, 3 | Silty sand, black, shell fragments, wet below 1.5 metres | Silty sand, black, shell fragments, wet below 1.5 metres | | | | | | Silica sand | 2.0 | |
| 2.0 - 3.0 | D | | 1, 1, 1, 2 | Silt, trace sand, grey-black, wood debris below 2.0 metres | Silt, trace sand, grey-black, wood debris below 2.0 metres | | | | | | GW = 1.46 m (Nov. 10/05) | 1.46 | |
| 3.0 - 4.0 | E | | 8, 12, 7, 9 | no recovery | no recovery | | | | | | Silica sand | 0.0 | |
| 4.0 - 5.0 | F | | 1, 4, 3, 3 | SILTY SAND Dark grey, shell fragments | SILTY SAND Dark grey, shell fragments | | | | | | Bentonite seal | -1.0 | |
| 5.0 - 5.18 | G | | 1, 2, 3, 2, 5 | SILT Light brown and grey mottling | SILT Light brown and grey mottling | | | | | | | -2.0 | |
| <p>End of borehole at 5.18 m</p> <p>Well Completion Details: Screened interval from 0.9 m to 2.4 m below surface Elevation at top of pipe (TOP) = 2.934 m</p> <p>Groundwater Information: Depth to groundwater from TOP = 1.40 m (Nov. 10/05)</p> | | | | | | | | | | | | | |

SEACOR CANADA V5 205.03066 BH - PRINCESS MARY.GPJ SEACOR CANADA V5.GDT 1/23/06

DRILLING METHOD: Split Spoon

Notes: SPLIT SPOON

DRILL DATE: February 17, 2005 LOGGED BY: AH

Sheet 1 of 1