

| DEPTH (m) | SAMPLE TYPE | SAMPLE ID | SPT COUNT | SOIL TYPE | SOIL DESCRIPTION | FIELD TEST DATA | | | | WELL COMPLETION | WATER LEVEL | WELL COMPLETION NOTES | ELEVATION (m) |
|------------|-------------|-----------|-----------|--------------|--|-----------------------------|----|-----|------|-----------------|-------------|-----------------------------|---------------|
| | | | | | | ORGANIC VAPOUR LEVEL (ppmv) | | | | | | | |
| | | | | | | 1 | 10 | 100 | 1000 | | | | |
| 0.0 - 0.5 | A | | | ASPHALT FILL | light brown silty SAND occasional gravel, damp | | | | | | | roadbox, plug, cement | 99 |
| 0.5 - 1.0 | B | | | | metal debris | | | | | | | bentonite seal | 98 |
| 1.0 - 1.5 | C | | | SILT | grey-brown, mottled, trace sand, damp | | | | | | | 10/20 filter sand | 98 |
| 1.5 - 2.0 | D | | | CLAY | grey-brown, firm to soft, trace silt, moist | | | | | | | GW = 97.45 m (July 9, 2004) | 97 |
| 2.0 - 2.5 | E | | | | | | | | | | | 50 mm Ø10 slot PVC pipe | 96 |
| 2.5 - 3.0 | F | | | | | | | | | | | | 95 |
| 3.0 - 4.57 | | | | | End of borehole at 4.57 m | | | | | | | | |
| | | | | | Screened Interval from 1.52 to 4.57 metres below surface Depth to Groundwater = 1.82 metres below ground surface (July 9, 2004) | | | | | | | | |

SEACOR CANADA V5 205.03059 ROMEO'S.GPJ SEACOR CANADA V5.GDT 2/25/05

DRILLING METHOD: Solid Stem Auger Drilling

Notes: AUGER SAMPLE

DRILL DATE: June 29, 2004

LOGGED BY: AH