

SSID	BGC ZONE	BGC SUBZONE	BGC VARIANT	BEC SITE SERIES	REGEN OBLIGATION IND	REGEN DELAY OFFSET YRS	FREE GROWING LATE OFFSET YRS	TARGET STOCKING (TSS)	MIN STOCKING STANDARD (MSS)	MIN PREF STOCKING STANDARD (MSSp)	MIN HORIZONTAL DISTANCE - MITD (m)	HGHT RELATIVE TO COMPETITION (%)	PREFERRED SPECIES	ACCEPTABLE SPECIES	ADDITIONAL STANDARDS
1050859	CWH	dm		1	Y	6	20	900	500	400	2	150	FDC(3.0) CW(1.5) HW(3.0)	PW(2.5)	(HW24) ; HW-suitable (as a major species) in wetter portion of biogeoclimatic unit; (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. Do not use non-resistant stock for reforestation. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050860	CWH	dm		3	Y	6	20	800	400	400	2	150	FDC(2.0)	CW(1.0) HW(2.0)	MITD is 2.0m exceptas describe in Part V - Stocking Standards in the FSP.
1050862	CWH	dm		4	Y	6	20	900	500	400	2	150	FDC(3.0)	CW(1.5) PW(2.5)	(PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. Do not use non-resistant stock for reforestation. Associated with red-listed plant communities. MITD is 2.0m exceptas describe in Part V - Stocking Standards in the FSP.
1050863	CWH	dm		5	Y	6	20	900	500	400	2	150	CW(2.0) FDC(4.0)	PW(2.5)	(PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050864	CWH	dm		6	Y	6	20	900	500	400	2	150	CW(1.5) HW(3.0)	FDC(3.0)	(FDC1) ; FDC-elevated microsities are preferredAssociated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050865	CWH	dm		7	Y	6	20	900	500	400	2	150	CW(2.0) FDC(4.0)		MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050866	CWH	dm		8	Y	6	20	900	500	400	2	150	BG(3.5) CW(2.0)		Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050867	CWH	dm		9	Y	6	20	900	500	400	2	150	CW(2.0)	BG(3.5)	(CW1) ; CW-elevated microsities are preferred; (BG1) ; BG-elevated microsities are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050868	CWH	dm		12	Y	6	20	800	400	400	2	150	CW(1.0)	HW(2.0) PW(2.5) SS(3.0)	(CW1) ; CW-elevated microsities are preferred; (HW1) ; HW-elevated microsities are preferred; (HW2) ; HW-suitable on thick forest floors; (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. ; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	1	1	Y	6	20	900	500	400	2	150	FDC(3.0) CW(1.5)	HW(2.0) PW(2.5) BA(0.7) SS(3.0) YC(1.5)	(HW10) ; HW-restricted to northerly aspects. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. (YC) ; YC Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	1	2	Y	6	20	800	400	400	2	150	PL(1.25) FDC(2.0)	CW(1.0) PW(2.5) YC(1.0)	MITD is 2.0m except as described in Part V - Stocking Standards in the FSP. (PW) PW-Do not plant Pw due to risk of white pine blister rust, rely on natural regeneration for this species is acceptable.
TBD	CWH	mm	1	3	Y	6	20	800	400	400	2	150	FDC(2.0)	CW(1.0) HW(1.7) PL(1.2) PW(2.5) YC(2.0)	MITD is 2.0m except as described in Part V - Stocking Standards in the FSP. (PW) PW-Do not plant Pw due to risk of white pine blister rust, rely on natural regeneration for this species is acceptable. (YC) YC- Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites.
TBD	CWH	mm	1	4	Y	6	20	900	500	400	2	150	FDC(2.0)	CW(1.0) PW(2.5) HW(1.7) YC(1.0)	(PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP. (YC) ; YC Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites.
TBD	CWH	mm	1	5	Y	6	20	900	500	400	2	150	FDC(3.0) CW(1.5)	PW(2.5) BA(0.7) SS(3.0) HW(2.0), YC(1.5)	Associated with red-listed plant communities. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. (SS) SS restricted to shaded sites and/or in conjunction with ACT DR MB sites. (YC) ; YC-Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	1	6	Y	6	20	900	500	400	2	150	CW(1.5) HW(2.0)	FDC(3.0) BA(0.7) PW(2.5) SS(3.0) YC(1.5)	Associated with red-listed plant communities. (FDC7) ; FDC-restricted to nutrient-medium sites. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. (YC) ; YC-Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	1	7	Y	6	20	900	500	400	2	150	CW(2.0) FDC(4.0)	BA(1.0) SS(4.0) HW(2.5) PW(2.5) YC(2.0)	MITD is 2.0m except as described in Part V - Stocking Standards in the FSP. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. (YC) ; YC-Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites.

SSID	BGC ZONE	BGC SUBZONE	BGC VARIANT	BEC SITE SERIES	REGEN OBLIGATION IND	REGEN DELAY OFFSET YRS	FREE GROWING LATE OFFSET YRS	TARGET STOCKING (TSS)	MIN STOCKING STANDARD (MSS)	MIN PREF STOCKING STANDARD (MSSp)	MIN HORIZONTAL DISTANCE - MITD (m)	HGHT RELATIVE TO COMPETITION (%)	PREFERRED SPECIES	ACCEPTABLE SPECIES	ADDITIONAL STANDARDS
TBD	CWH	mm	1	8	Y	6	20	900	500	400	2	150	BA(1.0) CW(2.0) SS(4.0)	FDC(4.0) HW(2.5) YC(2.0)	(SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP. (YC) ; YC-Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites.
TBD	CWH	mm	1	9	Y	6	20	900	500	400	2	150	CW(2.0)	BA(1.0) SS(4.0) HW(2.5) YC(2.0)	(CW1) ; CW-elevated microsities are preferred; (BA1) ; BA-elevated microsities are preferred. (YC) ; YC-Restricted to areas influenced by CWHvm2 or CWHvh1, or to cold air drainage sites. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	1	Y	6	20	900	500	400	2	150	HM(1.0) HW(1.25) CW(1.0) FDC(2.25) YC(1.0)	BA(0.75) BP(1.5) PW(2.5)	(FDC9) ; FDC-restricted to southerly aspects; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	2	Y	6	20	800	400	400	2	150	PL(1.25) FDC(1.5)	CW(0.75) PW(2.5) HM(0.7) HW(1.0) YC(0.7)	(HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	3	Y	6	20	800	400	400	2	150	FDC(1.5) HW(1.0)	HM(0.75) CW(0.75) YC(0.75) PW(2.5) PL(1.2)	(HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	4	Y	6	20	900	500	400	2	150	FD(1.5)	CW(0.75) PW(2.5) YC(0.75) Hm(0.7) Hw(1.0) Pl(1.2)	(HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	5	Y	6	20	900	500	400	2	150	BA(0.75) CW(1.0) FDC(2.25) YC(1.0)	BP(1.0) PW(2.5) HM(1.2) HW(1.2)	(FDC9) ; FDC-restricted to southerly aspects; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	6	Y	6	20	900	500	400	2	150	HW(1.25) CW(1.0) YC(1.0)	BA(0.75) HM(1.25) FDC(2.25) HW(1.2) PW(2.5)	(HM13) ; HM-restricted to upper elevations of biogeoclimatic unit; (FDC14) ; FDC-restricted to the lower elevations of the biogeoclimatic unit; (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	7	Y	6	20	800	400	400	2	150	BA(0.75) CW(0.75) HW(1.0)	HM(0.75) YC(0.75) FDC(1.5) PW(2.5)	(CW1) ; CW-elevated microsities are preferred; (YC1) ; YC-elevated microsities are preferred; (FDC1) ; FDC-elevated microsities are preferred (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
TBD	CWH	mm	2	8	Y	6	20	900	500	400	2	150	BA(1.0) CW(1.25) YC(1.25)	HW(1.75) FDC(3.0) HM(1.2)	(FDC9) ; FDC-restricted to southerly aspects; MITD is 2.0m except as described in Part V - Stocking Standards in the FSP.
1050869	CWH	ms	2	1	Y	6	20	900	500	400	2	150	FDC(2.3) CW(1.0)	BA(.8) HW(1.0)	(BA10) ; BA-restricted to northerly aspects; (HW10) ; HW-restricted to northerly aspects. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050870	CWH	ms	2	3	Y	6	20	800	400	400	2	150	FDC(2.3) PLC(1.0) CW(1.0)	HW(1.0)	MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050871	CWH	ms	2	4	Y	6	20	900	500	400	2	150	BA(1.0) FDC(3.0) HW(1.3)	CW(1.3) SS(4.0)	(BA10) ; BA-restricted to northerly aspects; (BA13) ; BA-restricted to upper elevations of biogeoclimatic unit; (HW10) ; HW-restricted to northerly aspects; (SS17) ; SS-restricted to western portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050872	CWH	ms	2	5	Y	6	20	900	500	400	2	150	HW(1.0) BA(.8)	CW(1.0)	(BA10) ; BA-restricted to northerly aspects; (BA13) ; BA-restricted to upper elevations of biogeoclimatic unit MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050873	CWH	ms	2	6	Y	6	20	900	500	400	2	150	BA(1.0) CW(1.3) FDC(3.0)	SS(4.0)	(BA10) ; BA-restricted to northerly aspects; (BA13) ; BA-restricted to upper elevations of biogeoclimatic unit; (SS17) ; SS-restricted to western portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.

SSID	BGC ZONE	BGC SUBZONE	BGC VARIANT	BEC SITE SERIES	REGEN OBLIGATION IND	REGEN DELAY OFFSET YRS	FREE GROWING LATE OFFSET YRS	TARGET STOCKING (TSS)	MIN STOCKING STANDARD (MSS)	MIN PREF STOCKING STANDARD (MSSp)	MIN HORIZONTAL DISTANCE - MITD (m)	HGHT RELATIVE TO COMPETITION (%)	PREFERRED SPECIES	ACCEPTABLE SPECIES	ADDITIONAL STANDARDS
1050874	CWH	ms	2	7	Y	6	20	900	500	400	2	150	BA(1.0) CW(1.3)	SS(4.0)	(SS17) ; SS-restricted to western portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050875	CWH	ms	2	8	Y	6	20	900	500	400	2	150	CW(1.3)	BA(1.0)	(CW1) ; CW-elevated microsities are preferred; (BA1) ; BA-elevated microsities are preferred MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050876	CWH	ms	2	11	Y	6	20	800	400	400	2	150	CW(.8)	HW(.8) SS(2.0)	(CW1) ; CW-elevated microsities are preferred; (HW1) ; HW-elevated microsities are preferred; (SS1) ; SS-elevated microsities are preferred; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050877	CWH	vh	1	1	Y	6	20	900	500	400	2	150	CW(1.5) HW(2.0) YC(1.5)	BA(1.8) PLC(1.5) SS(3.0)	(BA7) ; BA-restricted to nutrient-medium sites; (PLC6) ; PLC-restricted to nutrient-very-poor sites; (SS7) ; SS-restricted to nutrient-medium sites; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050947	CWH	vh	1	3	Y	6	20	800	400	400	2	150	CW(1.0) HW(1.3) PLC(1.3) YC(1.0)	SS(3.0)	MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050878	CWH	vh	1	4	Y	6	20	900	500	400	2	150	BA(2.3) HW(1.8) CW(2.0)	SS(4.0)	(SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050949	CWH	vh	1	5	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) YC(2.0) SS(4.0)	HW(1.8)	(HW2) ; HW-suitable on thick forest floors; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except where limited by: residual harvesting debris providing coarse woody debris including slash at roadsites or within debris piles, or in heli-harvested stands; mechanical site prepared areas (including areas stump treated for root disease); hygric, sub-hydric or other soil limiting conditions. Where the above limitations occur, MITD may be reduced to 1.6m.
1050948	CWH	vh	1	6	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) YC(2.0) SS(4.0)	HW(1.8)	(HW2) ; HW-suitable on thick forest floors; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050950	CWH	vh	1	7	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) SS(4.0)	HW(1.8)	(HW2) ; HW-suitable on thick forest floors; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050879	CWH	vh	1	8	Y	6	20	900	500	400	2	150	CW(2.0) SS(4.0)	BA(2.3)	Associated with red-listed plant communities. MITD is 2.0m except where limited by: residual harvesting debris providing coarse woody debris including slash at roadsites or within debris piles, or in heli-harvested stands; mechanical site prepared areas (including areas stump treated for root disease); hygric, sub-hydric or other soil limiting conditions. Where the above limitations occur, MITD may be reduced to 1.6m.
1050880	CWH	vh	1	9	Y	6	20	900	500	400	2	150	SS(4.0) CW(2.0)	BA(2.3)	(SS1) ; SS-elevated microsities are preferred; (CW1) ; CW-elevated microsities are preferred; (BA1) ; BA-elevated microsities are preferredAssociated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050951	CWH	vh	1	11	Y	6	20	800	400	400	2	150	CW(1.0) HW(1.3) PLC(1.3) YC(1.0)	SS(3.0)	(CW1) ; CW-elevated microsities are preferred; (HW1) ; HW-elevated microsities are preferred; (PLC6) ; PLC-restricted to nutrient-very-poor sites; (YC1) ; YC-elevated microsities are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050952	CWH	vh	1	13	Y	6	20	800	400	400	2	150	CW(1.0) YC(1.0)	HW(1.3) PLC(1.3) SS(2.0)	(CW1) ; CW-elevated microsities are preferred; (HW1) ; HW-elevated microsities are preferred; (PLC7) ; PLC-restricted to nutrient-medium sites. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050881	CWH	vh	2	1	Y	6	20	900	500	400	2	150	CW(1.5) HW(2.0) YC(1.5)	BA(1.8) PLC(1.5) SS(3.0)	(BA7) ; BA-restricted to nutrient-medium sites; (SS7) ; SS-restricted to nutrient-medium sites. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050882	CWH	vh	2	3	Y	6	20	800	400	400	2	150	CW(1.0) HW(1.3) PLC(1.3) YC(1.0)		MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050883	CWH	vh	2	4	Y	6	20	900	500	400	2	150	BA(2.3) HW(1.8) SS(4.0) CW(2.0)	YC(2.0)	MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050885	CWH	vh	2	5	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) SS(4.0)	HW(1.8) YC(2.0)	(HW2) ; HW-suitable on thick forest floors. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050884	CWH	vh	2	6	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) SS(4.0)	HW(1.8) YC(2.0)	(HW2) ; HW-suitable on thick forest floors MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050886	CWH	vh	2	7	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) SS(4.0)	HW(1.8) YC(2.0)	(HW2) ; HW-suitable on thick forest floors.MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.

SSID	BGC ZONE	BGC SUBZONE	BGC VARIANT	BEC SITE SERIES	REGEN OBLIGATION IND	REGEN DELAY OFFSET YRS	FREE GROWING LATE OFFSET YRS	TARGET STOCKING (TSS)	MIN STOCKING STANDARD (MSS)	MIN PREF STOCKING STANDARD (MSSp)	MIN HORIZONTAL DISTANCE - MITD (m)	HGHT RELATIVE TO COMPETITION (%)	PREFERRED SPECIES	ACCEPTABLE SPECIES	ADDITIONAL STANDARDS
1050887	CWH	vh	2	8	Y	6	20	900	500	400	2	150	CW(2.0) SS(4.0)	BA(2.3) HW(1.8)	Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050888	CWH	vh	2	9	Y	6	20	900	500	400	2	150	SS(4.0) CW(2.0)	BA(2.3)	(SS1) ; SS-elevated microsites are preferred; (CW1) ; CW-elevated microsites are preferredAssociated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050889	CWH	vh	2	11	Y	6	20	800	400	400	2	150	CW(1.0) HW(1.3) YC(1.0)	PLC(1.3)	(CW1) ; CW-elevated microsites are preferred; (HW1) ; HW-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (PLC1) ; PLC-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050890	CWH	vh	2	13	Y	6	20	800	400	400	2	150	CW(1.0) YC(1.0)	HW(1.3)	(CW1) ; CW-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (HW1) ; HW-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050953	CWH	vm	1	1	Y	6	20	900	500	400	2	150	CW(1.5) HW(3.0) FDC(3.0) BA(1.8)	SS(3.0)	(FDC9) ; FDC-restricted to southerly aspects; (FDC16) ; FDC-restricted to southern portion of biogeoclimatic unit in region; (BA26) ; BA-suitable minor species on salal-dominated sites. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050891	CWH	vm	1	3	Y	6	20	800	400	400	2	150	CW(1.0) HW(2.0) FDC(2.0)	PLC(1.3)	(FDC9) ; FDC-restricted to southerly aspects; (FDC16) ; FDC-restricted to southern portion of biogeoclimatic unit in region; (PLC53) ; PLC-minor component. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050943	CWH	vm	1	4	Y	6	20	900	500	400	2	150	CW(1.5) HW(3.0) FDC(3.0)	SS(3.0)	(FDC9) ; FDC-restricted to southerly aspects; (FDC16) ; FDC-restricted to southern portion of biogeoclimatic unit in region. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050892	CWH	vm	1	5	Y	6	20	900	500	400	2	150	BA(1.8) CW(1.5) HW(3.0) FDC(3.0)	SS(3.0)	(FDC1) ; FDC-elevated microsites are preferred; (FDC9) ; FDC-restricted to southerly aspects; (FDC16) ; FDC-restricted to southern portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050944	CWH	vm	1	6	Y	6	20	900	500	400	2	150	BA(1.8) CW(1.5) HW(3.0)	SS(3.0)	(BA26) ; BA-suitable minor species on salal-dominated sites. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050893	CWH	vm	1	7	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) FDC(4.0) HW(4.0)	SS(4.0)	(FDC1) ; FDC-elevated microsites are preferred; (FDC9) ; FDC-restricted to southerly aspects; (FDC23) ; FDC- restricted to trial use; (HW2) ; HW-suitable on thick forest floors; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050894	CWH	vm	1	8	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) HW(4.0)	SS(4.0)	(HW2) ; HW-suitable on thick forest floors; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050895	CWH	vm	1	9	Y	6	20	900	500	400	2	150	BA(2.3) CW(2.0) HW(4.0)	SS(4.0)	(SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050896	CWH	vm	1	10	Y	6	20	900	500	400	2	150	CW(2.0)	BA(2.3) SS(4.0)	(CW1) ; CW-elevated microsites are preferred; (BA1) ; BA-elevated microsites are preferred; (SS1) ; SS-elevated microsites are preferred; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050897	CWH	vm	1	12	Y	6	20	800	400	400	2	150	CW(1.0) HW(2.0) YC(1.0)	PLC(1.3)	(CW1) ; CW-elevated microsites are preferred; (HW1) ; HW-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (PLC1) ; PLC-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050898	CWH	vm	1	14	Y	6	20	800	400	400	2	150	CW(1.5)	HW(3.0) SS(3.0)	(CW1) ; CW-elevated microsites are preferred; (HW1) ; HW-elevated microsites are preferred; (SS1) ; SS-elevated microsites are preferred; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050899	CWH	vm	2	1	Y	6	20	900	500	400	2	150	FDC(2.3) HW(2.5) CW(1.5) YC(1.5) BA(1.8)	HM(1.0) SS(3.0)	(FDC1) ; FDC-elevated microsites are preferred; (FDC9) ; FDC-restricted to southerly aspects; (FDC23) ; FDC-Restricted to trial use; (YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit; (SS7) ; SS-restricted to nutrient-medium sites; (SS16) ; SS-restricted to southern portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.

SSID	BGC ZONE	BGC SUBZONE	BGC VARIANT	BEC SITE SERIES	REGEN OBLIGATION IND	REGEN DELAY OFFSET YRS	FREE GROWING LATE OFFSET YRS	TARGET STOCKING (TSS)	MIN STOCKING STANDARD (MSS)	MIN PREF STOCKING STANDARD (MSSp)	MIN HORIZONTAL DISTANCE - MITD (m)	HGHT RELATIVE TO COMPETITION (%)	PREFERRED SPECIES	ACCEPTABLE SPECIES	ADDITIONAL STANDARDS
1050900	CWH	vm	2	3	Y	6	20	800	400	400	2	150	CW(1.0) HW(1.8) FDC(1.5) YC(1.0)	HM(.8) PLC(1.3) PW(2.5)	(FDC9) ; FDC-restricted to southerly aspects; (FDC16) ; FDC-restricted to southern portion of biogeoclimatic unit in region; (YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit; (PLC53) ; PLC-minor component; (PW16) ; PW-restricted to southern portion of biogeoclimatic unit in region; (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050945	CWH	vm	2	4	Y	6	20	900	500	400	2	150	CW(1.0) HW(1.8) FDC(1.5) YC(1.0)	BA(1.5) PW(2.5) HM(.8) SS(2.0)	(FDC9) ; FDC-restricted to southerly aspects; (FDC16) ; FDC-restricted to southern portion of biogeoclimatic unit in region; (YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (PW16) ; PW-restricted to southern portion of biogeoclimatic unit in region; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050901	CWH	vm	2	5	Y	6	20	900	500	400	2	150	CW(1.5) HW(2.5) YC(1.5) BA(1.8)	FDC(2.3) SS(3.0) HM(1.0)	(YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (FDC1) ; FDC-elevated microsites are preferred; (FDC8) ; FDC-restricted to steep slopes; (FDC9) ; FDC-restricted to southerly aspects; (FDC23) ; FDC-restricted to trial use; (SS16) ; SS-restricted to southern portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. ; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050902	CWH	vm	2	6	Y	6	20	900	500	400	2	150	CW(1.5) HW(2.5) YC(1.5) BA(1.8)	HM(1.0) SS(3.0)	(YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit; (SS7) ; SS-restricted to nutrient-medium sites. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050903	CWH	vm	2	7	Y	6	20	900	500	400	2	150	CW(2.0) HW(3.5) YC(2.0) BA(2.3)	SS(4.0) HM(1.0)	(HW2) ; HW-suitable on thick forest floors; (YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (SS16) ; SS-restricted to southern portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. ; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050904	CWH	vm	2	8	Y	6	20	900	500	400	2	150	CW(2.0) HW(3.5) YC(2.0) BA(2.3)	SS(4.0) HM(1.0)	(CW14) ; CW- restricted to the lower elevations of the biogeoclimatic unit; (HW2) ; HW-suitable on thick forest floors; (HW30) ; HW-risk of porcupine damage; (YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (SS16) ; SS-restricted to southern portion of biogeoclimatic unit in region; (SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. ; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050905	CWH	vm	2	9	Y	6	20	800	400	400	2	150	CW(1.0) HW(1.8) YC(1.0)	BA(1.5) HM(.8)	(CW1) ; CW-elevated microsites are preferred; (HW1) ; HW-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unitMITD is 2.0m except where limited by: residual harvesting debris providing coarse woody debris including slash at roadsites or within debris piles, or in heli-harvested stands; mechanical site prepared areas (including areas stump treated for root disease); hygic, sub-hydric or other soil limiting conditions. Where the above limitations occur, MITD may be reduced to 1.6m.
1050946	CWH	vm	2	11	Y	6	20	800	400	400	2	150	CW(1.0) YC(1.0)	HW(1.8) SS(2.0)	(CW1) ; CW-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (YC69) ; YC-Species is restricted to upper elevations when used in the southern portion of the biogeoclimatic unit.; (HW1) ; HW-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050906	CWH	ws	2	1	Y	6	20	900	500	400	2	150	BA(.8) BL(.8) HW(1.0) CW(1.0)	SXS(.8) HM(1.0)	(BL12) ; BL-suitable on cold air drainage sites; (SXS35) ; SXS-risk of weevil damage; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit; (HM53) ; HM-minor component. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050907	CWH	ws	2	3	Y	6	20	800	400	400	2	150	HW(1.0) PLC(2.0) CW(1.0) FDC(1.5)	HM(1.0)	(FDC9) ; FDC-restricted to southerly aspects; (FDC14) ; FDC- restricted to the lower elevations of the biogeoclimatic unit; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit; (HM53) ; HM-minor component MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.

SSID	BGC ZONE	BGC SUBZONE	BGC VARIANT	BEC SITE SERIES	REGEN OBLIGATION IND	REGEN DELAY OFFSET YRS	FREE GROWING LATE OFFSET YRS	TARGET STOCKING (TSS)	MIN STOCKING STANDARD (MSS)	MIN PREF STOCKING STANDARD (MSSp)	MIN HORIZONTAL DISTANCE - MITD (m)	HGHT RELATIVE TO COMPETITION (%)	PREFERRED SPECIES	ACCEPTABLE SPECIES	ADDITIONAL STANDARDS
1050908	CWH	ws	2	4	Y	6	20	900	500	400	2	150	BA(1.0) BL(1.0) CW(1.3)	HW(1.3) HM(1.0) SXS(1.0)	(BL12) ; BL-suitable on cold air drainage sites; (HM13) ; HM-restricted to upper elevations of biogeoclimatic unit; (HM53) ; HM-minor component; (SXS35) ; SXS-risk of weevil damage. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050909	CWH	ws	2	5	Y	6	20	900	500	400	2	150	BA(.8) CW(1.0) HW(1.0)	BL(.8)	(BL12) ; BL-suitable on cold air drainage sites. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050910	CWH	ws	2	6	Y	6	20	900	500	400	2	150	BA(1.0) BL(1.0) CW(1.3)	HW(1.3) SXS(1.0)	(BL12) ; BL-suitable on cold air drainage sites; (HW2) ; HW-suitable on thick forest floors; (SXS35) ; SXS-risk of weevil damage. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050911	CWH	ws	2	7	Y	6	20	900	500	400	2	150	BA(1.0) CW(1.3)	BL(1.0) HW(1.3) SXS(1.0)	(BL12) ; BL-suitable on cold air drainage sites; (SXS35) ; SXS-risk of weevil damage. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050912	CWH	ws	2	8	Y	6	20	900	500	400	2	150	CW(1.3) DR(4.0)	BA(1.0) BL(1.0) SXS(1.0)	(CW1) ; CW-elevated microsities are preferred; (BA1) ; BA-elevated microsities are preferred; (BL12) ; BL-suitable on cold air drainage sites; (SXS1) ; SXS-elevated microsities are preferred; (SXS35) ; SXS-risk of weevil damage. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050913	CWH	ws	2	11	Y	6	20	800	400	400	2	150	CW(.8)	SXS(.6) HW(.8)	(CW1) ; CW-elevated microsities are preferred; (SXS1) ; SXS-elevated microsities are preferred; (HW1) ; HW-elevated microsities are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050914	CWH	xm		1	Y	6	20	900	500	400	2	150	FDC(3.0)	HW(2.0) CW(1.5) PW(2.5)	(HW24) ; HW-suitable (as a major species) in wetter portion of biogeoclimatic unit; (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050915	CWH	xm		3	Y	6	20	800	400	400	2	150	FDC(2.0) PLC(1.3)	CW(1.0)	(PLC6) ; PLC-restricted to nutrient-very-poor sites. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050916	CWH	xm		4	Y	6	20	900	500	400	2	150	FDC(3.0)	CW(1.5) PW(2.5)	(PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050917	CWH	xm		5	Y	6	20	900	500	400	2	150	CW(2.0) FDC(4.0)	PW(2.5)	(PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050918	CWH	xm		6	Y	6	20	900	500	400	2	150	CW(1.5) HW(2.0) FDC(3.0)		(FDC18) ; FDC-restricted to eastern portion of biogeoclimatic unit in regionAssociated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050919	CWH	xm		7	Y	6	20	900	500	400	2	150	CW(2.0) FDC(4.0)	BG(3.5)	Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050920	CWH	xm		8	Y	6	20	900	500	400	2	150	CW(2.0) SS(4.0)	BG(3.5)	(SS35) ; SS-risk of weevil damage. Use stock with the highest resistance rating for your area. Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050921	CWH	xm		9	Y	6	20	900	500	400	2	150	CW(2.0)	BG(3.5)	(CW1) ; CW-elevated microsities are preferred; (BG1) ; BG-elevated microsities are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050922	CWH	xm		12	Y	6	20	800	400	400	2	150	CW(1.0)	HW(1.3) PW(2.5)	(CW1) ; CW-elevated microsities are preferred; (HW1) ; HW-elevated microsities are preferred; (PW31) ; PW-Risk of white pine blister rust. Do not use non-resistant stock for reforestation. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050923	CWH	xm		13	Y	6	20	900	500	400	2	150	CW(2.0) BG(3.5) FDC(4.0)		Associated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050924	CWH	xm		14	Y	6	20	900	500	400	2	150	BG(3.5) CW(2.0)		(BG1) ; BG-elevated microsities are preferred; (CW1) ; CW-elevated microsities are preferredAssociated with red-listed plant communities. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050925	CWH	xm		15	Y	6	20	800	400	400	2	150	CW(2.0)		(CW1) ; CW-elevated microsities are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050927	MH	mm	1	1	Y	7	20	900	500	400	2	125	BA(.6) HM(1.0) YC(1.0)	SE(1.0)	(SE23) ; SE-restricted to max 20% of well spaced P&A. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050928	MH	mm	1	2	Y	6	20	800	400	400	2	125	HM(.8) YC(.8)	BA(.6) SE(.8)	(SE23) ; SE-restricted to max 20% of well spaced P&A. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050929	MH	mm	1	3	Y	6	20	900	500	400	2	125	BA(.6) HM(1.0) YC(1.0)		MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050930	MH	mm	1	4	Y	7	20	900	500	400	2	125	BA(.6) HM(1.0) YC(1.0)		MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050931	MH	mm	1	5	Y	6	20	900	500	400	2	125	BA(.6) YC(1.0)	HM(1.0)	MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.

SSID	BGC ZONE	BGC SUBZONE	BGC VARIANT	BEC SITE SERIES	REGEN OBLIGATION IND	REGEN DELAY OFFSET YRS	FREE GROWING LATE OFFSET YRS	TARGET STOCKING (TSS)	MIN STOCKING STANDARD (MSS)	MIN PREF STOCKING STANDARD (MSSp)	MIN HORIZONTAL DISTANCE - MITD (m)	HGHT RELATIVE TO COMPETITION (%)	PREFERRED SPECIES	ACCEPTABLE SPECIES	ADDITIONAL STANDARDS
1050932	MH	mm	1	6	Y	7	20	800	400	400	2	125	HM(.8) YC(.8)	BA(.6)	(HM1) ; HM-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (BA1) ; BA-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050933	MH	mm	1	7	Y	6	20	900	500	400	2	125	BA(.6) YC(.8)	HM(.8)	(BA1) ; BA-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (HM1) ; HM-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050934	MH	mm	1	9	Y	6	20	800	400	400	2	125	YC(.8)	HM(.8)	(YC1) ; YC-elevated microsites are preferred; (HM1) ; HM-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050935	MH	mm	2	1	Y	7	20	900	500	400	2	125	BA(.6) HM(1.0) YC(1.0) SE(1.0)		(YC17) ; YC-restricted to western portion of biogeoclimatic unit in region. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050936	MH	mm	2	2	Y	6	20	440	400	400	2	125	BL(.8) HM(.8) SE(.8) YC(.8)	BA(.6)	(BL45) ; BL-suitable in areas with stronger continental influence; (BL53) ; BL-minor component; (YC17) ; YC-restricted to western portion of biogeoclimatic unit in region. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050937	MH	mm	2	3	Y	6	20	900	500	400	2	125	BA(.6) HM(1.0) SE(1.0) YC(1.0)		(YC17) ; YC-restricted to western portion of biogeoclimatic unit in region. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050938	MH	mm	2	4	Y	7	20	900	500	400	2	125	BA(.6) HM(1.0) YC(1.0)		(YC17) ; YC-restricted to western portion of biogeoclimatic unit in region. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050939	MH	mm	2	5	Y	6	20	900	500	400	2	125	BA(.6) SE(1.0) YC(1.0)	HM(1.0)	(YC17) ; YC-restricted to western portion of biogeoclimatic unit in region. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050940	MH	mm	2	6	Y	7	20	800	400	400	2	125	HM(.8) YC(.8)	BA(.6)	(HM1) ; HM-elevated microsites are preferred; (YC17) ; YC-restricted to western portion of biogeoclimatic unit in region; (BA1) ; BA-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050941	MH	mm	2	7	Y	6	20	900	500	400	2	125	BA(.6) SE(.8) YC(.8)	HM(.8)	(BA1) ; BA-elevated microsites are preferred; (SE1) ; SE-elevated microsites are preferred; (YC17) ; YC-restricted to western portion of biogeoclimatic unit in region; (HM1) ; HM-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.
1050942	MH	mm	2	9	Y	6	20	800	400	400	2	125	HM(.8) YC(.8)	SE(.8)	(HM1) ; HM-elevated microsites are preferred; (YC1) ; YC-elevated microsites are preferred; (YC17) ; YC-restricted to western portion of biogeoclimatic unit in region; (SE1) ; SE-elevated microsites are preferred. MITD is 2.0m except as describe in Part V - Stocking Standards in the FSP.