



REFER TO DWG 03 FOR GROUTED SHEAR KEY DETAILS

TYPICAL BRIDGE SECTION

1:30

1. GENERAL

- 1.1 THESE PRESTRESSED CONCRETE SLAB GIRDER DRAWINGS ILLUSTRATE THE FOLLOWING PRIMARY GIRDER VARIATION (ALL BRIDGES HAVE 4 GIRDERS):
 - BRIDGE WIDTH: 4.3m OR 4.9m
 - SHEAR KEYS: GROUTED OR FIELD WELDED OR NO SHEAR KEYS.
- 1.2 ALL GIRDERS HAVE TWO VOIDS/GIRDER.
- 1.3 BRIDGE TO BE CLEARLY AND PERMANENTLY IDENTIFIED IN ACCORDANCE WITH SECTION 4.3 OF FOREST SERVICE BRIDGE DESIGN AND CONSTRUCTION MANUAL. LETTERING TO BE AT LEAST 50mm HIGH.
- 2. DESIGN CRITERIA
 - 2.1 DESIGN CONFORMS TO CAN/CSA-S6-88 "DESIGN OF HIGHWAY BRIDGES" WITH VARIATIONS LIMITED TO SECTION 3 OF FOREST SERVICE BRIDGE DESIGN AND CONSTRUCTION HANDBOOK.
 - 2.2 DESIGN VEHICLES ARE L-75, L-100 L-150 OR L-165 DESIGN LOGGING TRUCKS. REFER TO FOREST SERVICE BRIDGE DESIGN AND CONSTRUCTION MANUAL FOR DESIGN VEHICLE LOADING DETAILS.
 - 2.3 DESIGN VEHICLES HAVE TWO LIMITING LATERAL ECCENTRICITIES:
 - E1: 400mm OFF CENTERLINE
 - E2: OUTSIDE WHEEL 600mm FROM GUARDRAIL
 - 2.4 LIMIT STATE LOAD CASES FOR E1 AND E2:
 - SERVICEABILITY: E1 (EXCEPT FATIGUE)
 - ULTIMATE: E1 AND E2
 - 2.5 ONE LINE OF WHEELS ASSUMED TO BE 60% OF TOTAL AXLE WEIGHT FOR E1 AND E2.
 - 2.6 DYNAMIC LOAD ALLOWANCE 30%.
 - 2.7 FATIGUE DESIGN IS FOR 500,000 CYCLES OF DESIGN VEHICLE ON BRIDGE CENTRELINE WITH BALANCED LOADING (50/50 WHEELS).
 - 2.8 MAXIMUM GIRDER LIVE LOAD SERVICEABILITY LIMIT STATE DEFLECTION SPAN/350. MAXIMUM DIFFERENTIAL DEFLECTION BETWEEN ADJACENT GIRDERS WITH NO SHEAR KEYS IS 30mm.
 - 2.9 MAXIMUM SERVICEABILITY REINFORCEMENT FATIGUE STRESS RANGE 161 MPa (ONTARIO HIGHWAY BRIDGE DESIGN CODE CLAUSE C8-5.3.1 THIRD EDITION)
 - 2.10 NO TENSILE IN-SERVICE STRESSES PERMITTED IN TOP FLANGE.
 - 2.11 GIRDERS WITH WELDED SHEAR KEYS DESIGNED TO CARRY ONE LINE OF WHEELS (60% TOTAL AXLE WEIGHT) IN THE EVENT OF FAILURE OF SHEAR KEY WELDS.
 - 2.12 THE SERVICEABILITY LIFE OF THE WELDED SHEAR KEYS IS UNCERTAIN AND WILL PROBABLY BE LESS THAN 50 YEARS. WELDS SHOULD BE INSPECTED REGULARLY AND WELD FAILURES REPAIRED.

ASSUME NOT TO SCALE

3. CONCRETE

- 3.1 REFER TO TABLE 2 (DWG 03), TABLE 10 (DWG 04) AND TABLE 18 (DWG 05). FOR CONCRETE STRENGTH AT 28 DAYS.
- 3.2 MINIMUM CONCRETE STRENGTH IS 30 MPa FOR RELEASE OF STRANDS, ERECTION OF GIRDERS OR PASSAGE OF UNLOADED LOGGING TRUCKS.
- 3.3 BOTTOM EDGES OF GIRDERS CHAMFERED 20mm.
- 3.4 TOP OF GIRDERS TO HAVE TRANSVERSE BROOM FINISH OR FLOAT FINISH AS SPECIFIED.
- 3.5 GIRDER ERECTION WEIGHTS BASED ON AVERAGE DENSITY OF 2500 kg/m³.
- 3.6 HARDWARE GALVANIZING (WHERE SPECIFIED) - 2 COATS OF GALVAICON.

4. GROUT

- 4.1 GROUT TO BE NON-SHRINK WITH MINIMUM 28 DAY STRENGTH OF 30 MPa.
- 4.2 USE TARGET PORTLAND EXPANDING GROUT OR APPROVED EQUAL FOR NORMAL TEMPERATURES (10 DEG C OR WARMER).
- 4.3 USE EMACO T415 GROUT OR APPROVED EQUAL FOR COLDER TEMPERATURES (COLDER THAN 10 DEG C).
- 4.4 GROUT TO BE PREBAGGED AND MIXED AND PLACED IN ACCORDANCE WITH MANUFACTURER'S PROCEDURES.
- 4.5 MAXIMUM AGGREGATE SIZE 10mm.

5. PRESTRESSING STEEL

- 5.1 ALL STRANDS TO BE 13mm DIA LOW RELAXATION STRAND, 1862 MPa GRADE.
- 5.2 MINIMUM STRAND ULTIMATE TENSILE STRENGTH 184 KN/STRAND.
- 5.3 STRAND FORCE IMMEDIATELY AFTER RELEASE 138 KN/STRAND.
- 5.4 FULLY BONDED STRANDS USED. DEBONDING MAY BE USED WHEN APPROVED.
- 5.5 EXPOSED ENDS OF STRAND TO BE COATED WITH TWO COATS OF GALVAICON.

6. REINFORCING STEEL

- 6.1 REINFORCING STEEL TO BE DEFORMED BARS CONFORMING TO CSA G30.18 GRADE 400.
- 6.2 NO WELDING OR MECHANICAL SPLICING OF REINFORCING PERMITTED.
- 6.3 LONGITUDINAL BAR SPLICES TO BE STAGGERED SO THAT NO MORE THAN EVERY THIRD BAR IS SPLICED AT ANY GIVEN SECTION.

7. TRANSPORTATION AND ERECTION

- 7.1 GIRDERS TRANSPORTED AND HANDLED WITH GIRDER TOP FLANGE (SHEAR KEYS) ALWAYS FACING UPWARDS. MANUFACTURER TO CHECK HANDLING STRESSES.
- 7.2 GIRDERS MUST BE SUPPORTED WITHIN 1 METRE OF BEARING LOCATIONS DURING TRANSPORTATION, STORAGE AND ERECTION (NO LAUNCHING).
- 7.3 LIFTING DEVICES SHALL COMPRISE LIFTING LOOPS OF 13mm DIA PRESTRESSING STRAND, 1862 MPa GRADE. STRAND TO BE CUT OFF 50mm BELOW CONCRETE SURFACE AND COATED WITH TWO COATS OF GALVAICON. HOLE AROUND STRAND TO BE GROUTED. ALTERNATIVE LIFTING DEVICES MUST BE APPROVED PRIOR TO USE.
- 7.4 ONLY LOW IMPACT LIFTS ARE PERMITTED. ANGLE OF LIFT MUST NOT EXCEED 30 DEGREES FROM VERTICAL.

<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Rev</th> <th style="width: 10%;">Date</th> <th style="width: 60%;">Description</th> <th style="width: 10%;">Init</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>	Rev	Date	Description	Init																													<p>SCALE</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">DESIGNED BY: GWT</td> <td style="width: 20%;">DATE: MAR/99</td> </tr> <tr> <td>CHECKED BY: GWT</td> <td>DATE: MAR/99</td> </tr> <tr> <td>DRAWN BY: DG</td> <td>DATE: MAR/99</td> </tr> </table>	DESIGNED BY: GWT	DATE: MAR/99	CHECKED BY: GWT	DATE: MAR/99	DRAWN BY: DG	DATE: MAR/99	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;"> Province of British Columbia MINISTRY OF FORESTS RESOURCE TENURES AND ENGINEERING BRANCH </td> </tr> <tr> <td colspan="2" style="text-align: center;"> STANDARD BRIDGE DRAWING </td> </tr> <tr> <td colspan="2" style="text-align: center;"> PRECAST PRESTRESSED CONCRETE SLAB GIRDERS GENERAL NOTES </td> </tr> <tr> <td style="width: 70%;">ORIGINAL DESIGNED AND SEALED BY: GRAHAM W. TAYLOR, P.ENG.</td> <td style="width: 30%;"> MPE ENGINEER </td> </tr> <tr> <td>DESIGN ENGINEER: GRAHAM W. TAYLOR, P.ENG.</td> <td>MPE ENGINEER</td> </tr> <tr> <td>DATE: _____</td> <td>DATE: _____</td> </tr> <tr> <td>FILE NO.:</td> <td>DRAWING NO.:</td> </tr> </table>	Province of British Columbia MINISTRY OF FORESTS RESOURCE TENURES AND ENGINEERING BRANCH		STANDARD BRIDGE DRAWING		PRECAST PRESTRESSED CONCRETE SLAB GIRDERS GENERAL NOTES		ORIGINAL DESIGNED AND SEALED BY: GRAHAM W. TAYLOR, P.ENG.	 MPE ENGINEER	DESIGN ENGINEER: GRAHAM W. TAYLOR, P.ENG.	MPE ENGINEER	DATE: _____	DATE: _____	FILE NO.:	DRAWING NO.:																			
	Rev	Date	Description	Init																																																																						
DESIGNED BY: GWT	DATE: MAR/99																																																																									
CHECKED BY: GWT	DATE: MAR/99																																																																									
DRAWN BY: DG	DATE: MAR/99																																																																									
Province of British Columbia MINISTRY OF FORESTS RESOURCE TENURES AND ENGINEERING BRANCH																																																																										
STANDARD BRIDGE DRAWING																																																																										
PRECAST PRESTRESSED CONCRETE SLAB GIRDERS GENERAL NOTES																																																																										
ORIGINAL DESIGNED AND SEALED BY: GRAHAM W. TAYLOR, P.ENG.	 MPE ENGINEER																																																																									
DESIGN ENGINEER: GRAHAM W. TAYLOR, P.ENG.	MPE ENGINEER																																																																									
DATE: _____	DATE: _____																																																																									
FILE NO.:	DRAWING NO.:																																																																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Rev</th> <th style="width: 10%;">Date</th> <th style="width: 60%;">Description</th> <th style="width: 10%;">Init</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>	Rev	Date	Description	Init																																	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Rev</th> <th style="width: 10%;">Date</th> <th style="width: 60%;">Description</th> <th style="width: 10%;">Init</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>	Rev	Date	Description	Init																																	<p style="text-align: right;"> STD-E-080-01 A </p> <p style="font-size: small; text-align: right;"> <small>CANCEL PRINTS BEARING PREVIOUS LETTER</small> </p>
Rev	Date	Description	Init																																																																							
Rev	Date	Description	Init																																																																							